

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T20-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Harvey Gordon, Deputy Surveyor, Under Contract #49, dated Oct. 17, 1854 - (DCSO records Vol. 2 Page(s) 677)

Set post corner of secs. 19, 24, 25 & 30; from which
A R.Fir 24" dia., bears N.49°E., 44 lks. dist.
A R.Fir 12" dia., bears S.65°E., 76 lks. dist.
a R.Fir 50" dia., bears N.72°W., 27 lks. dist.
A Redwood 18" dia., bears S.70°W., 42 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; C Putnam, crew - Jan. 1962 - C.S. File 49/89-24

Found - 12" Fir snag, S.65°E., 50.2 ft. scribing visible on old face, previously opened, "T2 R5W S30."
Fir tree, now 60", N.72°W., 17.8 ft., old bark scribing visible "T20S R6W S2."
I.Cedar, now 36", S.70°W., 27.7 ft., has been cut into but old face not exposed.

These 3 trees still in good condition. Distances noted to old face.

Set I.Pipe with brass cap mkd: Doug. County Surveyors Office

T 20 S
S 24 | S 19
S 25 | S 30
R 6 W | R 5 W
1962

New BT - 16" D.Fir S.60°E., 83.0 ft. mkd. T20S R5W S30 DCS BT.

Blaze and rescribe:

60" Fir N.72°W., 17.8 ft. "T20S R6W S24 DCS BT"

Fd. Corner OK in BLM Resurvey by Wm. Glenn, Cadastral Surveyor, Group #441, Surveyed June/July 1962 - (DCSO records Vol. 27 Page(s) 11324B)

"Added BLM 1962 to brass cap."

BLM Resurvey by Floyd Brooks and Timothy Kent, Cadastral Surveyors, under Group #648, Surveyed Aug/Sept. 1967 - (DCSO records Vol. 37 Page(s) 15269)

The cor. of secs. 19, 24, 25 and 30, monumented by Godfrey in 1962, with an iron post 1" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1962, from which the remains of the original bearing trees:

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T20-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 42" dia., bears N.49°E., 44 lks. dist., with fragmentary scribe marks visible on opened blaze.

A Fir snag 12" dia., bears S.65°E., 76 lks. dist. with scribe marks T R5W S30 visible on burned face of opened blaze.

A Cedar 37" dia., bears S.70°W., 42 lks. dist., with healed blaze. (Record, Redwood)

A broken Fir stump 60" dia., bears N.72°W., 27 lks. dist. with scribe marks T20S R6 S visible on badly scaled bark blaze. The DCSO remarked this tree "T20S R6W S24 DCS BT"

and a bearing tree mkd. by Godfrey:

A Fir 15" dia., bears S.60°E., 126 lks. dist., with pitched over blaze.

and new bearing trees:

A Fir 23" dia., bears S.23°E., 166 lks. dist. with pitched over blaze.

A Fir 18" dia., bears N.54¼°W., 156 lks. dist. mkd. T20S R6W S24 BT.

BLM Resurvey by Daniel N. Patterson & Craig L. Wanless, Cadastral Surveyors, under Group #1764, surveyed Jan/May 1995 - (DCSO records Vol. 52 Page(s) 19700-01)

The Sec. cor., monumented with an iron pipe, 1¼" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1962, from which the remains of the original bearing trees:

A Fir 51" dia., bears N.49°E., 46½ lks. dist. with healed blaze.

A Fir snag, 10" dia., bears S.65°E., 76 lks. dist. with scribe marks T20S R5W S30 visible on open blaze.

A Cedar 45" dia., bears S.70°W., 42 lks. dist. with healed blaze.

A Fir snag, 58" dia., bears N.72°W., 27 lks. dist. with scribe marks T20S R5W S24 DCS BT visible on open blaze.

and a bearing tree mkd. by DCSO and reported by Glenn:

A Fir 23" dia., bears S.59 3/4°E., 125 lks. dist. with healed blaze.

and bearing trees mkd. by person(s) unknown:

A Fir 34" dia., bears S.22 3/4°E., 165 lks. dist., with healed blaze.

A Fir 28" dia., bears N.54¼°W., 155 lks. dist. with healed blaze.

(Note: The above 2 trees appear to be the same as new BTs mkd. by Brooks and Kent in 1967. V.Laugen, Sept. 1997)