

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated Aug. 1, 1883 (DCSO records Vol. 1 Page(s) 455-56)

-----  
Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for gr. sec. cor., marked ¼ S on W. face; from which  
A Fir 48" dia., bears West, 25 lks. dist. mkd. ¼ S BT.  
A Fir 36" dia., bears S.60°E., 36 lks. dist. mkd. ¼ S BT.

Fd. OK and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 577)

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #292, Surveyed June/Oct. 1950 - (DCSO records Vol. 27 Page(s) 11329-330)

-----  
The ¼ sec.cor., determined at the record bearing from each of the original bearing trees as follows:

- A Fir 50" dia., bears S.60°E., 38 lks. dist. mkd. on the bark BT ¼. (Rec. 36 lks. dist.)
- A Fir 66" dia., bears West, 26 lks. dist. with partial scribe marks visible on the bark. (Rec. 25 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

¼ S 36 |  
1950

from which new bearing trees

- A Hemlock 12" dia., bears S.37¼°W., 41 lks. dist. mkd. ¼ S36 BT.
- A Fir 12" dia., bears N.28°W., 127 lks. dist. mkd. ¼ S36 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16699)

-----  
The ¼ sec. cor., monumented with an iron post 1" dia., firmly set, projecting 10" above ground, with brass cap mkd. in 1950, from which the remains of the original bearing trees:

- A burned and dead Fir 55" dia., bears S.60°E., 38 lks. dist., no marks visible on burned blaze.
- A burned and sawed Fir stump 70" dia., bears West, 26 lks. dist., no marks visible on burned blaze.

and the remains of the bearing trees mkd. in 1950:

(Cont. Next Page)

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 100121

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burned Hemlock 15" dia., bears S.37¼°W., 41 lks. dist., no marks visible on burned blaze. Rescribed ¼ S36 BT on new blaze.

A burned and sawed Fir stump 11" dia., bears N.28°W., 127 lks. dist., with burned blaze. Rescribed ¼ S36 BT on new blaze.

Set a 5 ft. steel fence post alongside iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21747)

-----  
The ¼ sec. cor. of sec. 36 only, monumented with an iron post, 1" dia., firmly set, projecting 8" above the ground with brass cap (properly) mkd.

from with the remains of the original bearing trees

A fir snag, 55" dia., bears S.60°E., 25.1 ft., to face, no marks visible.

A fir stump, 65" dia., bears West, 17.2 ft., no marks visible.

and new bearing trees

A fir, 14" dia., bears S.61¾°W., 12.9 ft., mkd. ¼ S36 BT.

A fir, 15" dia., bears N.48°W., 25.4 ft., mkd. X BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.