

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated Aug. 1, 1883 (DCSO records Vol. 1 Page(s) 456)

-----  
Set post 6" dia., 4 ft. long, with mkd. stone 12" in ground, for cor. to secs. 25 & 36, mkd. T20S R7W S31 on E.; T20S R8W CC S36 on SW.; S25 on NW. faces, with 5 notches on N. and 1 notch on S. edges; from which

Fir 24" dia., bears N.54°E., 58 lks. dist. mkd. T20S R7W S31 BT.

Maple 16" dia., bears N.77°W., 72 lks. dist. mkd. T20S R8W S25 BT CC.

Fir 24" dia., bears S.17°W., 73 lks. dist. mkd. T20S R8W S36 BT CC.

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 577)

-----  
The cor. to secs. 25 & 36, which is a post, 6" dia., firmly set in the ground and marked T20S R7W S31 on E.; T20S R8W CC S36 on SW.; S25 on NW. faces, with 1 notch on S. & 5 notches on N. edge; from which

A Fir 24" dia., bears N.54°E., 58 lks. dist. mkd. T20S R7W S31 BT.

A Maple 16" dia., bears N.77°W., 12 lks. dist. (Not 72 lks.), mkd. T20S R8W S25 BT CC.

A Fir 24" dia., bears S.17°W., 73 lks. dist. mkd. T20S R8W S36 BT CC.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #292, Surveyed June/Oct. 1950 - (DCSO records Vol. 27 Page(s) 11330)

-----  
The sec. cor., determined at the record bearing from the orig. SW. bearing tree and the record bearing and distance from the original NW. bearing tree as follows:

A Fir 40" dia., bears S.17°W., 63 lks. dist., plainly blazed and healed. (Record, 73 lks. dist.)

A Maple 22" dia., bears N.77°W., 12 lks. dist., plainly blazed and healed. (Wright's record, 72 lks. dist.; Todd's record, 12 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S	T 20 S
S 25	
S 36	R 7 W
R 8 W	S 31

1950 (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36, T20-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which a new bearing tree:  
A Hemlock 10" dia., bears N.12½°W., 67 lks. dist. mkd.  
T20S R8W S25 BT.

---

BLM Resurvey by Lynn M. Roseberry & Wm. Glenn, Cadastral Surveyors - Under Group's #350 & 622 Surveyed, Oct. 1966/May 1967 - (DCSO records Vol. 34 Page(s) 14137)

-----

The sec. cor., monumented with an iron post, 2" dia., protruding 12" above the ground, firmly set, with brass cap mkd. in 1950, from which the remaining original bearing trees mkd. by Wright:

A stump hole bears S.17°W., 63 lks. dist., with burned and fallen Fir lying alongside, 40" dia., with no marks remaining.

A burned twin Maple 40" dia., bears N.77°W., 12 lks. dist. with a healed blaze.

and a bearing tree mkd. by Tillman in 1950:  
A burned Hemlock 17" dia., bears N.12½°W., 67 lks. dist. with illegible scribe marks visible on burned and partially healed blaze.

and a new bearing tree:  
A burned Fir 28" dia., bears S.26½°W., 130 lks. dist. mkd. T20S R8W S36 BT.

Set a steel fence post alongside the iron post.

---

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21747-8)

-----

The cor. of secs. 25 & 36 only, monumented with an iron post, 2" dia., firmly set, projecting 14" above the ground, with brass cap (properly) mkd. from which the remains of an original bearing tree

A root hole with maple remains bears N.77°W., 7.9 ft. and the remains of a bearing tree mkd. by Roseberry and Glenn in 1966-67

A fir snag, 29" dia., bears S.26½°W., 85.8 ft., with a healed blaze.

and new bearing trees

A fir, 16" dia., bears S.44¼°W., 38.7 ft., mkd. T20S R8W S36 BT.

A fir, 14" dia., bears N.9¼°W., 19.2 ft., mkd. T20S R8W S25 BT.

There is a steel fence post alongside the corner. Each new bearing tree has a 2½" x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

cont.

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 100162

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. as per 2005 BLM remon., set 6 ft. steel post S.1°W., 2 ft.; by D. Edwards 1/2015 - M169-1