

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #'s 350 & 622, Surveyed Oct. 1966/May 1967 - (DCSO records Vol. 34 Page(s) 14148)

-----  
Point for the ¼ sec. cor. of sec. 30 only, at midpoint latitudinally, on the W. bdy. of sec. 30.  
Set an iron post, 15" long, 1" dia., 5" in drill hole in solid sandstone, with brass cap mkd:

T 20 S  
¼S 30  
R 7 W

1966

from which

A sandstone boulder 10x6x10 ft. above ground, bears N.63½°E., 40 lks. dist. mkd. X BO on W. face.

A sandstone boulder 8x5x6 ft. above ground, bears S.19½°E., 59 lks. dist. mkd. X BO on N. face.

Set a steel fence post alongside the iron post.

Ronald Rice - For: Oxbow Timber 1 LLC - Sept. 2015 - M170-15A&B

-----  
Found - GLO brass cap dated 1966

Sandstone bolder 10x6x10' above ground bears N.63½°E., 26.4' - record marks not fd.

Sandstone bolder 8x5x6' above ground bears S.19½°E., 38.9' - marked X BO

New - 11" D.Fir bears N.5°E., 5.7' blazed, scribed S30 BT

12" D.Fir bears N.68°W. 13.4' blazed, scribed X BT

14" D.Fir bears S.5°W., 19.4' blazed, scribed X BT

Steel post adjacent to corner.