

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 456-57)

Set post 6" dia., 4 ft. long, with marked stone, 12" in ground for cor. to secs. 24 & 25, marked T20S R7W S30 on E.; T20S R8W S25 CC on SW.; S24 CC on NW. faces, with 4 notches on N. & 2 on S. edges; from which

Fir 12" dia., bears S.31°E., 21 lks. mkd. T20S R7W S30 BT.
 Fir 30" dia., bears N.47°W., 71 lks. mkd. T20S R8W S24 BT.
 Fir 30" dia., bears S.71°W., 77 lks. mkd. T20S R8W S25 BT.

Fd. OK and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 578)

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #292, Surveyed June/Oct. 1950 - (DCSO records Vol. 27 Page(s) 11332)

The cor. of secs. 24 & 25, determined at the record bearing from the original SW. bearing tree and the record bearing and distance from the original NW. bearing tree as follows:

A Fir 56" dia., bears S.71°W., 81 lks. dist., plainly blazed and healed. (Rec. 77 lks. dist.)
 A dead Fir 36" dia., bears N.47°W., 71 lks. dist., with partial scribe marks visible on the bark.

At the corner point
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S	T 20 S
S 24	R 7 W
S 25	S 30
R 8 W	1950

from which a new bearing tree
 A Fir 60" dia. bears N.55°W., 126 lks mkd. T20S R8W S24 BT

BLM Resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #'s 350 & 622, Surveyed Oct. 1966/May 1967 - (DCSO records Vol. 34 Page(s) 14138)

The Sec. Cor., monumented with an iron post 2" dia., protruding 10" above the ground, firmly set, with brass cap marked in 1950,
 from which the remaining original bearing trees mkd. by Wright

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burned Fir 60" dia., bears S.71°W., 84 lks. with burned out blaze, no scribe marks visible. (Rec. dist 81 lks.)
 A burned Fir snag 25" dia., bears N.47°W., 71 lks. no marks remaining.
 and a bearing tree mkd. by Tillman in 1950:
 A burned Fir 67" dia., bears N.55¾°W., 123½ lks. mkd. with a healed blaze. (Rec. brg. and dist., N.55°W., 126 lks)
 Set a steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21748-9)

The cor. of secs. 24 and 25 only, monumented with an iron post, 2" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.
 from with the remains of the original bearing trees
 A decayed fir stump, 41" dia., bears S.71°W. 55.4 ft. w/no marks visible on partially healed blaze. (Rec 53.5 ft)
 A decayed fir stump, 27" dia., bears N.47°W., 46.9 ft., no marks visible.
 and the remains of a bearing tree mkd. by Tillman in 1950
 A decayed fir stump, 65" dia., bears N.55°W., 81.5 ft., no marks visible. (Record, 83.2 ft.)
 and new bearing trees
 A fir, 12" dia., bears S.71¾°W., 39.7 ft., mkd. T20S R8W S25 BT.
 A fir, 13" dia., bears N.13¾°W., 11.1 ft., mkd. T20S R8W S24 BT.
 Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Ronald L. Rice, Ward NW Inc. - Jason Collier - Feb. 13, 2012 - C.S. File 65/76-19

Found - BLM brass cap, 1950 w/the following accessories:
 12" D.Fir bears S.71¾°W., 39.7' - healed face
 15" D.Fir bears N.13¾°W., 11.1' - healed face
 41" Decayed D.Fir stump bears S.71°W., 55.4' - no marks visible
 27" Decayed D.Fir stump bears N.47°W., 46.9' - no marks visible
 65" Decayed D.Fir stump bears N.55°W., 81.5' - no marks visible

Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.
 Compass Declination 16° East

Cont.

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 100261

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald L Rice - For: Oxbow Timber 1 LLC - Sept 2015 - M170-15A&B

Found - GLO brass cap dated 1950
12" D.Fir bears S.71 $\frac{3}{4}$ °W., 39.7' - healed face.
15" D.Fir bears N.13 $\frac{1}{4}$ °W., 11.1' - healed face.
and other accessories as noted in CS 65/76-19
Steel post adjacent to corner.