

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 30 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 622-623)

(At a point 19 chs. N.1°E. of old cor to S. 24 & 25, T20-8)
I set a sandstone 16x12x12 ins., 12" in the ground for closing cor. to secs. 19 & 30, marked C C with 2 notches on S. & 4 notches on N. faces; from which
A Fir 40" dia., bears N.23°E., 20 lks. dist. mkd. T20S R7W S19 BT.
A Fir 30" dia., bears S.47°E., 70 lks. dist. mkd. T20S R7W S30 BT.
A Maple 5" dia., bears N.40°W., 43 lks. dist. mkd. T20S R7W CC S19 & 30 BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12341)

The closing cor., monumented with a shattered sandstone 16x12x12 ins., loosely set 12" in the ground, from which the remaining original bearing trees:

A Fir snag 40" dia., bears S.47°E., 70 lks. dist., with marks BT 7W visible on remaining portion of bark blaze.
A Maple 12" dia., bears N.40°W., 43 lks. dist., with no marks visible on open blaze. (Rec. dist., 48 lks.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S		T 20 S	
S 24		S 19	CC
		S 30	
R 8 W		R 7 W	
		1954	

from which new bearing trees:

A Fir 50" dia., bears N.50½°E., 52 lks. dist. mkd. T20S R7W S19 CC BT.
A Hemlock 8" dia., bears S.17°E., 44 lks. dist. mkd. T20S R7W S30 CC BT.

BLM Resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #'s 350 & 622, Surveyed Oct. 1966/May 1967 - (DCSO records Vol. 34 Page(s) 14139)

The original closing cor., monumented with an iron post 2" dia., protruding 10" above the ground, firmly set, with brass cap mkd. in 1954, from which the remaining original bearing tree mkd. by Todd:
(Cont. Next Page)

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION C.C. for Secs. 19 & 30 only (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A burned Maple 12" dia., bears N.40°W., 43 lks. dist., with burned out blaze, no scribe mark visible. and bearing trees mkd. by Tillman in 1954:
A burned Fir 48" dia., bears N.50½°E., 52 lks. dist., with illegible scribe marks visible on partially healed and burned blaze.
A burned Hemlock 10" dia., bears S.17°E., 44 lks. dist. with illegible scribe marks visible on partially healed and burned blaze.
and a new bearing tree:
A burned Fir 37" dia., bears S.38°E., 79 lks. dist., mkd. T20S R7W S30 BT.
Set a steel fence post alongside the iron post.

Ron Rice, NW Land Surveying - Oct. 2013 - C.S. File 65/80-22 & M167-70 (3/2014)

Found - 2½" GLO brass cap, dated 1954, with the following accessories:
Burned Maple 12" dia., bears N.40°W., 43 lks., with burned out blaze, no scribe mark visible. (Missing)
Burned Fir 48" dia., bears N.50½°E., 52 lks., with illegible scribe marks visible on partially healed and burned blaze. (Found 48" fir stump, scribing visible)
Burned Hemlock 10" dia., bears S.17°E., 44 lks. with illegible scribe marks visible on partially healed and burned blaze. (Missing)
Burned Fir 37" dia., bears S.38°E., 79 lks., mkd. T20S R7W S30 BT. (Fd 37" fir stump, no marks)
New - 17" D. Fir bears S.4°E., 15.2 ft. - blazed, scribed T20S R7W S30 CC BT
15" D. Fir bears N.81°E., 20.0 ft. - blazed, scribed T20S R7W S19 CC BT
Note - Corner has steel post adjacent to it. All live BTs have red painted bands and yellow tags.
Compass Declination 16° East

Fd. BC, 2 BTs, and other accessories as noted on M167-70 9/2015, by Ron Rice, M170-15A&B