

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 458)

Set post 4" dia., 4 ft. long, 12" in ground with marked stone, for gr. sec.cor., marked ¼ S on W. face, from which
Fir 48" dia., bears N.12°E., 25 lks. dist. mkd. ¼ S BT.
Fir 45" dia., bears N.67°W., 28 lks. dist. mkd. ¼ S BT.

Fd. OK, and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 579)

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12343)

The ¼ sec. cor., determined at record distance from the original bearing trees:

A Fir 60" dia., bears N.12°E., 25 lks. dist., mkd. ¼ S BT on bark.

A Fir 66" dia., bears N.73°W., 28 lks. dist., partial marks visible on bark. (Rec. brg. N.67°W.)

At the corner point

Set an iron post, 3 ft. long, 1" dia., 24" in the ground, with brass cap mkd:

¼ S 13*
*

1954

from which a new bearing tree:

A Fir 58" dia., bears S.89°W., 37 lks. dist. mkd. ¼ S13 BT

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16700-01)

The ¼ sec. cor., monumented with an iron post, 1" dia., firmly set, projecting 3" above ground, with brass cap mkd. in 1954,

from which the original bearing trees:

A Fir 60" dia., bears N.12°E., 25 lks. dist., no marks remaining on burned blaze.

A Fir 66" dia., bears N.73°W., 28 lks. dist., no marks remaining on burned blaze.

and a bearing tree mkd. in 1954:

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Fir 58" dia., bears S.89°W., 37 lks. dist., no marks remaining on burned blaze. Rescribed "¼ S13 BT" on new blaze.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21749-50)

The ¼ sec. cor. of sec. 13 only, monumented with an iron post, 1" dia., firmly set, projecting 3" above the ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

- A burned decayed fir stump, 48" dia., bears N.12°E., 16.5 ft., no marks visible.
- A burned decayed fir stump, 70" dia., bears N.73°W., 23.9 ft., no marks visible. (Record, 18.5 ft.)

and the remains of a BT mkd. by Tillman, et al., in 1953-54

- A burned decayed fir stump, 53" dia., bears S.89°W., 24.4 ft., no marks visible.

and new bearing trees

- A fir, 15" dia., bears S.23½°W., 13.8 ft., mkd. ¼ S13 BT.
- A fir, 12" dia., bears N.86°W., 11.4 ft., mkd. X BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Ron Rice, NW Land Surveying - Nov. 2013 - C.S. File 65/82-11 & M167-67 (3/2014)

Found - 2½" GLO brass cap, dated 1954, with the following accessories:

- Burned decayed fir stump, 48" dia., bears N.12°E., 16.5 ft., no marks visible. (found same)
- Burned decayed fir stump, 70" dia., bears N.73°W., 23.9 ft., no marks visible. (Found same)
- Burned decayed fir stump, 53" dia., bears S.89°W., 24.4 ft., no marks visible. (Found same)
- Fir, 15" dia., bears S.23½°W., 13.8 ft., mkd. ¼ S13 BT. (Found 15" D. Fir with healed face)
- Fir, 12" dia., bears N.86°W., 11.4 ft., mkd. X BT. (Found 13" D. Fir with healed face and healed chopped X at breast height)

New - 15" D. Fir bears S.28°E., 7.7 ft. - blazed, scribed X BT.

Note - Corner has steel post adjacent to it. All live BTs have red painted bands and yellow tags. Declination 16° East.