

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only (West)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 627-28)

-----  
(At a point, 18.30 chs. N.1°E. of cor. to secs. 12, 13, 7 & 18)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for closing cor. to secs. 7 & 18, marked CC T20S R7W on E., S7 on N.; S18 on S. faces, with 4 notches on S. & 2 notches on N. faces; from which

- A Fir 24" dia., bears N.66°E., 10 lks. dist., mkd. T20S R7W S7 BT.
- A Yew 7" dia., bears S.47°E., 37 lks. dist., mkd. T20S R7W S18 BT.
- A Dogwood 7" dia., bears S.87°W., 31 lks. dist. mkd. T20S R7W S7 & 18 BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12344-45)

-----  
The closing cor., monumented with a badly decayed Cedar post, 3" sq., rotted away 6" above ground, from which bearing trees, that do not match the record:

- A Fir snag, 28" dia., bears N.54°E., 37 lks. dist., with partial scribe marks visible on old bark blaze. (Rec. calls for a Fir, 24" dia., bearing N.66°E., 10 lks. dist.)
- A Fir 38" dia., bears S.49½°E., 44 lks. dist. mkd. BT S18 T20S R7W in bark. (Rec. calls for a Yew 7" dia., bearing S.47°E., 37 lks. dist.)
- A Fir snag 34" dia., bears S.33°E., 10 lks. dist., with partial scribe marks visible on scaled bark blaze.
- A Fir 28" dia., bears S.87°W., 31 lks. dist., plainly blazed and healed. (Rec. calls for a Dogwood, 7" dia.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S\*T 20 S  
S 12 <sup>\*S 7</sup>/<sub>\*S 18</sub> CC  
R 8 W\*R 7 W  
1954

from which a new bearing tree:

- A Hemlock 8" dia., bears N.39 3/4°E., 27 lks. dist., mkd. T20S R7W S7 CC BT.

continued next page

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only (West)

Alias	Description

Ron Rice - Feb. 28, 2013 - C.S. File 65/78-14

- 
- Found - A 2½" GLO brass cap on iron pipe, dated 1954  
Fir snag, 28" dia., bears N.54°E., 37 lks., with partial scribe marks visible on old bark blaze. (Missing)  
Fir 38" dia., bears S.49½°W E., 44 lks. mkd. BT S18 T20S R7W in bark. (Fd a 38" stump - no marks)  
Fir snag 34" dia., bears S.33°E., 10 lks., with partial scribe marks visible on scaled bark blaze. (Missing)  
Fir 28" dia., bears S.87°W., 31 lks., plainly blazed and healed. (Fd a 28"x5' burned fir stump)  
Hemlock 8" dia., bears N.39¼°E., 27 lks., mkd. T20S R7W S7 CC BT. (Missing)
- New - 17" D.Fir bears S.58°E., 5.9 ft. blazed, scribed, T20S R7W S18 CC BT  
20" D.Fir bears N.40°E., 24.3 ft. blazed, scribed, T20S R7W S7 CC BT  
19" D.Fir bears N 75°W., 7.8 ft. blazed, scribed, X BT  
18" D.Fir bears S.38°W., 22.8 ft. blazed, scribed, X BT
- Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.  
Declination 16° East