

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T20-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 459)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for cor. to secs. 12 & 1, marked T20S R7W S7 on E.; T20S R8W S12 CC on SW.; S1 CC on NW. faces, with 1 notch on N. and 5 on S. edges; from which
Fir 48" dia., bears N.47°E., 38 lks. dist., mkd. T20S R7W S7 BT.
Cedar 18" dia., bears S.28°W., 42 lks. dist. mkd. T20S R8W S12 BT.
Cedar 20" dia., bears N.64°W., 16 lks. dist. mkd. T20S R8W S1 BT.

Cor. Fd. OK, and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 580)

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12346)

The Sec. cor., determined at record bearing and distance from the remaining original bearing tree:
A Fir snag 50" dia., bears N.47°E., 38 lks. dist. mkd. with a healed blaze.
At the corner point
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S	T 20 S
S 1	R 7 W
S 12	S 7
R 8 W	
	1954

from which new bearing trees:
A Fir 60" dia., bears S.87½°W., 37 lks. dist., mkd. T20S R8W S12 BT.
A Fir 60" dia., bears N.36½°W., 64 lks. dist. mkd. T20S R8W S1 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16701-02)

The Sec. cor., monumented with an iron post, 2" dia., firmly (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T20-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

set, projecting 12" above ground, with brass cap mkd. in 1954,
from which the remains of the bearing trees mkd. in 1954:
A burned Fir, 58" dia., bears S.87½°W., 39 lks. dist., no marks remaining on burned blaze. (Rec. 37 lks.)
Rescribed "T20S R8W S12 BT" on new blaze.
A burned Fir 53" dia., bears N.36½°W., 68 lks. dist., no marks remaining on burned blaze. (Rec. 64 lks.)
Rescribed "T20S R8W S1 BT" on new blaze.

BLM Resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16089)

The Sec. cor., monumented with an iron post, 2" dia., firmly set, projecting 20" above ground, and in a mound of stone, 2 ft. base, 10" high, with brass cap mkd. in 1954, from which the remains of an original bearing tree:
A root hole bears N.47°E., 38 lks. dist., with a down Fir alongside, 50" dia., with healed blaze.
and the remains of bearing trees mkd. by Tillman, Bicknell, Thielsen and Gawron and rescribed by Glenn, White & Jelley:
A Fir 65" dia., bears S.87½°W., 37 lks. dist. with fragmentary scribe marks visible on burned and partially healed blaze, and rescribed T20S R8W S12 BT.
A sawed Fir stump 60" dia., bears N.36½°W., 64 lks. dist., no marks visible on open and burned blaze, and rescribed T20S R8W S1 BT.
No suitable trees available within limits.
Set a 5 ft. steel fence post alongside iron post.

Survey by Les Roberts - For: International Paper Co. - Dec. 1986 - M 103-63 & C.S. 63/46-3(A)

Found - A 1954 brass cap set loosely in the ground about 15 ft. down the hill from original position. Re-set brass cap from original BTs. Brass cap disturbed by logging activity.
A 30" Fir stump bears N.50°E., 25.1 ft., no marks. (1884 BT Rec. N.47°E., 25.1 ft.)
52" Fir stump bears N.36½°W., 43.0 ft., scribe visible. (1954 BT Rec. N.36½°W., 42.2 ft.)
58" Fir snag bears S.87½°W., 24.4 ft., scribe visible. (1954 BT Rec. S.87½°W., 24.4 ft.)
Set alum. fence post, with survey attention sign wired to, beside brass cap, painted all BTs red. Corner lies on N. slope about 250 ft. S. of North Sister Creek.

cont.

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 100563

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T20-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ron Rice - Feb. 28, 2013 - C.S. File 65/78-22

Found - A 1954 GLO brass cap
30" Fir stump bears N.50°E., 25.1 ft., no marks.
(Found same)
52" Fir stump bears N.36½°W. 43.0 ft scribe visible.
(Found same)
58" Fir snag bears S.87½°W., 24.4 ft scribe visible.
(Found same)
New - 10" D.Fir bears S.11°W., 11.8 ft. blazed, scribed,
T20S R8W S12 BT
19" D.Fir bears N.70°E., 14.1 ft. blazed, scribed,
T20S R8W S1 BT
11" D.Fir bears N.38°W., 33.2 ft. blazed, scribed,
X BT
Note - Corner has steel post adjacent to it. All BTs have
red painted bands and yellow tags.
Declination 16° East