

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, (West)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 629-30)

(At point of intersection, 18.20 chs. N.1°19'E. of cor. to secs. 1 & 12)

I set sandstone 16x11x11 ins., 12" in the ground, for closing cor. to secs. 6 & 7, marked CC with 5 notches on S. & 1 notch on N. faces; from which

A Fir 14" dia., bears N.13°W., 23 lks. dist., mkd. T20S R7W CC S6 & 7 BT.

A Fir 36" dia., bears N.60°E., 55 lks. dist., mkd. T20S R7W S6 BT.

A Fir 30" dia., bears S.15½°E., 77 lks. dist. mkd. T20S R7W S7 BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12346)

(Corner report only)

The Sec. cor., monumented with a shattered sandstone, 11x11 ins., 4" above ground, with no marks remaining from which the original bearing trees:

A Fir snag, 36" dia., bears N.60°E., 46 lks. dist., mkd. T20S R7W S6 BT. (Rec. dist. 55 lks.)

A Fir 48" dia., bears S.71°E., 73 lks. dist., mkd. with a healed blaze. (Rec. S.15p°E., 77 lks. dist.)

A Fir 34" dia., bears N.23°W., 23 lks. dist., mkd. with a healed blaze. (Rec. brg. N.13°W.)

BLM Resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16125-26)

(5.56 chs.)

The original closing cor. of secs. 6 & 7, determined from the remains of the original bearing trees:

A burned Fir stump 36" dia., bears N.60°E., 46 lks. dist., no marks visible. (Rec. 55 lks.)

A sawed and burned Fir stump 48" dia., bears S.71°E., 73 lks. dist., with healed blaze. (Rec. S.15½°E., 77 lks.)

A burned Fir stump 38" dia., bears N.23°W., 23 lks. dist., with healed blaze. (Rec. N.13°W.)

(N.89°38'W., 5.89 chs.)

True point for the closing cor. of secs. 6 & 7.

(Cont. Next Page)

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post 28" long, 2½" dia., 24" in the ground, with
brass cap mkd. T 20 S T 20 S

S 1 $\frac{S}{S} \frac{6}{7}$ CC

R 8 W R 7 W

1977

No suitable trees available within limits.

Set a 5 ft. steel fence post alongside iron post.

(From this point the cor. of secs. 1 & 12 only, T20S R8W,
bears S.1°18'W., 17.43 chs. dist.)