

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6 (NW Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 567-68)

I set a post 4½ ft.long, 4" sq., 24" in the ground, for closing cor. to Tps. 19 & 20 S., R7W., marked CC R7W on E. face, T19S S31 on N. face, T20S S6 on S. face, with 6 notches on each face; from which

- A Fir 30" dia., bears N.37°E., 40 lks. dist. mkd. T19S R7W S31 BT.
- A Cherry 10" dia., bears S.35°E., 29 lks. dist. mkd. T20S R7W S6 BT.
- A Hemlock 4" dia., bears S.61°W., 28 lks. dist. mkd. CC T19 & 20 S R7W BT.

GLO Resurvey by Norman Price and Thomas Tillman, Cadastral Engineers, under Group #284, Surveyed June/Sept. 1949 - (DCSO records Vol. 31 Page(s) 13011)

Set an iron post 3 ft. long, 3" dia., 28" in the ground with brass cap marked:

```

T 19 S T 19 S
      R 7 W
      S 36 S 31 _____ CC
            S 6
R 8 W T 20 S
      1949

```

from which

- A Fir 60" dia., bears N.11½°E., 35 lks. dist., plainly blazed and healed, an original bearing tree.
- A Hemlock 20" dia., bears S.31°E., 62 lks. dist. mkd. T20S R7W S6 CC BT.

From point of intersection, the original closing corner of Tps. 19 and 20 S., R 7 W., bears S.89°06'W., 17 lks. dist., determined at the record bearing and distance from the original NE. and SE. bearing trees which are as follows:

- A Fir 60" dia., bears N.37°E., 40 lks. dist., plainly blazed and healed.
- A Cherry 10" dia., dead and down, bears S.35°E., 29 lks. dist., with old blaze decayed.

BLM Resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16092-93)

The closing cor., monumented with an iron post 3" dia., firmly set, projecting 10" above ground with brass cap mkd. in 1949, from which the remains of bearing trees mkd. by Price and Tillman: (Cont. Next Page)

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6 (NW Tsp. Cor.)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A Fir snag, 60" dia., bears N.11½°E., 35 lks. dist., with healed blaze.
A Hemlock 31" dia., bears S.31°E., 62 lks. dist., with healed blaze.
and a new bearing tree:
A Fir 20" dia., bears N.41¼°E., 50½ lks. dist., mkd. T19S R7W S31 CC BT.
Set a 5 ft. steel fence post alongside the iron post.