

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 576)

Set post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which
A Fir 70" dia., bears N.30°E., 35 lks. dist. mkd. ¼ S BT
A Maple 6" dia., bears S.62°E., 88 lks. dist. mkd. ¼ S BT

Survey by Donald L. Branch, LS #1137 - For: International Paper Co. - Nov. 1983 - M 95-66

Found - 70" Fir laying 30 ft. down hill from root hole. Tree has burnt blaze with no visible scribing.
At record S.30°W., 23.1 ft. from root hole, I SET a 2½" I.D. alum. pipe protruding 6" above the ground with 3¼" alum. cap mkd. "T20S R7W ¼ S31 1983 PLS 1137".
New BTs- 7" Alder bears N.27°E., 11.1 ft. bark scribed ¼ S31 BT.
8" Alder bears S.26°W., 34.3 ft. scribed ¼ S6 BT.