

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 629)

-----  
Set post, 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., mkd: 1/4 S on N face; from which

A fir, 24" dia., bears S.31°W., 12 lks., mkd: 1/4 S BT.

A fir, 36" dia., bears N.20°E., 11 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #350 & 622, surveyed Oct. 1966/May 1967 (DCSO rec. Vol. 34 Page(s) 14157)

-----  
The 1/4 sec. cor. of secs. 6 & 7, determined at rec. bearing & distance from the orig. BTs:

A burned & dead fir, 40" dia., bears N.20°E., 11 lks., with scribe marks 1/4 S BT visible on open blaze.

A burned & dead fir, 32" dia., bears S.31°W., 12 lks., mkd. with a healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked: T20S R7W

1/4 S 6  
S 7

1967

Set a steel fence post alongside the iron post.

Found & used on BLM Resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16125)