

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 618)

-----  
Set post, 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on W face; from which

A fir, 48" dia., bears S.66°E., 44 lks., mkd: ¼ S BT.

A for, 66" dia., bears S.88°W., 38 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & BLM - Sept. 1966 - C.S. File 54/22-11

-----  
Found - Unrecorded Haines "T" iron & also, unrecorded Sandstone, 18"x14"x9" mkd: "¼" on W face, appears old.

Orig. 48", now 60" Fir S.66°E., 29.0 ft., slope dist. shows partial face on bark. Badly burned, no scribe found. Alive.

Orig. 66", now 68" S.88°W., 25.1 ft. slope dist. Has "¼S BT" bark scribe appears to be orig. No snag.

Rescribe Orig. SE BT "¼ S 20 CS BT"

Do not mark any new BTs at this time due to high rate of snags falling.

David Edwards - For: Oxbow Timber Co - 4/2014 - C.S. 65/81-16

-----  
Found - 60" Fir S.66°E., 29.0' slope distance.

68" Fir stump S.88°W., 25.1' slope distance.

Set - 5/8"x30" steel rebar with 2½" dia., alum. cap mkd: "ROSEBURG RESOURCES CO" as per 2009 BLM Manual and "LS 2014" set at position of T-Iron noted in 1966 DCS renewal of ¼ common to sections 31 & 32.

New - 12" dia., Fir scribed "T20S R7W ¼ S31 BT" bears S.56°W., 7.04 ft.

Set a 6 ft. steel post 2 ft. north.