

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 623-4)

Set a sandstone, 12x8x8, 8" in the ground, for cor. to secs. 17, 18, 19, & 20, marked with 3 notches on S & 5 notches on E edges; from which

- A maple, 15" dia., bears N.26°E., 11 lks., mkd: T20S R7W S17 BT.
- A maple, 36" dia., bears S.52°E., 81 lks., mkd: T20S R7W S20 BT.
- A fir, 36" dia., bears S.26°W., 27 lks., mkd: T20S R7W S19 BT.
- A maple, 20" dia., bears N.20°W., 32 lks., mkd: T20S R7W S18 BT.

Wilford N. Haines - For: Woolley Logging Co. - Filed April 1961 - M20-38

Found - 2 Orig. BTs, Maples gone.
Set - 1"x1"x36" T. iron.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage, J. Rabe, Frank Young - Sept 1966 - C.S. 54/22-9

Found - Haines "T" iron at corner.
Orig. 36" now 43" fir S.52°E., 53.5 ft., now burned stump, faint scar. We do not open
Orig. 36" now 48" fir S.14°W., 17.8 ft., recorded S.26°W. Open & find scribe marks.
No trace NE nor NW BTs

Set brass cap at point of intersection of distances from remaining BT.

Set - Brass cat at cor. mkd: County Surveyors Office 1966 T20S R7W S 18|S 17 S 19|S 20

Reset "T" alongside brass cap & red steel fence post
No live trees available for BTs, so rescribe originals.

48" fir stump S.14°W., 17.2 ft., mkd: T20S R7W S19 CS BT.

43" fir stump S.52°E., 53.5 ft., mkd: T20S R7W S20 CS BT.

Note - This corner lies on very steep N. slope on E-W cutting line.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM dependent resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #350 & 622, surveyed Oct. 1966/May 1967 (DCSO rec. Vol. 34 Page(s) 14155-6)

The cor. of secs. 17, 18, 19 & 20, perpetuated and recorded by Haines in 1961 monumented with a 1"x1" T-iron 36" long, with aluminum disc. mkd. WILFORD N. HAINES DRAIN OREGON 239 SURVEY POINT, and subsequently perpetuated and recorded by the Douglas County Surveyor in 1966, and monumented with an iron post 1" dia. firmly set projecting 8" above the ground with brass cap (properly) mkd from which original bearing trees

An uprooted maple, 16" dia., bears N.26°E., lks. with healed blaze.

A sawed and burned fir stump, 42" dia. bears S.52°E., 81 lks., with healed blaze and rescribed T20S R 7W S20 CS BT on new blaze.

A sawed and burned fir stump, 52" dia. .bears S.14°W., 30 lks.; with illegible scribe marks on partially opened blaze, and rescribed T20S R7W CS BT on new blaze. (rec. S.26°W., 27 lks.)

and new bearing trees

A burned fir snag, 32" dia., bears N.60°E. , 111 lks., mkd. T20S R7W S17 BT.

A burned fir snag, 45" dia., bears N.19°W., 111 lks., mkd. T20S R7W S18 BT .

Set a steel fence post alongside the iron post

Ron Rice - For: Oxbow Timber 1 LLC - 3/1/2013 - C.S. 65/79-4

Found - 1966 Douglas County Surveyors Office brass cap with the following accessories:

42" burned fir stump bears S.52°E., 53.5' scribing visible

52" burner fir stump bears S.14°W., 19.8' scribing visible

32" rotted fir stump bears N.60°E., 73.3' no marks

45" rotted fir stump bears N.19°W., 73.3' no marks

New BTs- 21" D.Fir bears N.62°E., 42.5' - blazed, scribed T20S R7W S17 BT

16" D.Fir bears N.77°W., 8.5' - blazed, scribed T20S R7 W S18 BT

13" D.Fir bears S.44°W., 20.0' - blazed, scribed T20S R7W S19 BT

16" D.Fir bears S.0½°E., 7.4' - blazed, scribed T20S R7W S20 BT

Steel post adjacent to corner

cont.

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2699, surveyed May/Sept 2013 - (DCSO records Vol. 58 page(s) 23145-6)

The cor. of secs. 17, 18, 19, and 20, perpetuated by Rice, in 2013, monumented with an iron post, 1¼" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

A burnt fir stump, 42" dia., bears S.52°E., 63.2 ft., with scribe marks S20 CS visible on an open blaze. (Record, 53.4 ft.)

A burnt fir stump, 44" dia., bears S.14°W., 23.0 ft., with scribe marks T20 R S visible on a partially healed blaze. (Record, 19.8 ft.)

and bearing trees mkd. by Rice

A fir, 20" dia., bears N.56¼°E., 42.5 ft., with scribe marks T20S R7W S18 BT visible on an open blaze.

A fir, 16" dia., bears S.2°E., 7.4 ft., with scribe marks T20S R7W S20 BT visible on an open blaze.

A fir, 12" dia., bears S.49°W., 20.0 ft., with scribe marks T20S R7W S19 BT visible on an open blaze.

A fir, 15" dia., bears N.71°W., 8.6 ft., with scribe marks T20S R7W S18 BT visible on an open blaze.

Alongside the cor. is a T-shaped iron rod, ¾" dia., firmly set, projecting 3" above ground.

NAD 1983 (2011)

Latitude: 43°49'20.53" N Longitude: 123°34'08.08"W

Ronald L Rice - For: Oxbow Timber 1 LLC - April 2015 - M170-3

Found - Douglas Co. brass cap dated 1966 with the following accessories:

42" Burnt D.Fir stump bears S.52°E., 63.2' - scribing visible.

44" burnt D.Fir stump bears S.14°W., 23.0' - scribing visible.

20" D.Fir bears N.56¼°E., 42.5' - scribing visible.

16" D.Fir bears S.2°E., 7.4' - scribing visible.

12" D.Fir bears S.49°W., 20.0' - scribing visible.

15" D.Fir bears N.71°W., 8.6' - scribing visible.

Steel post adjacent to corner.

Fd. BC & 4 BTs by Robert Cook - July 2019 - M175-71