

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 625-6)

Set V.Maple post, 4 ft. long, 4" sq., 2 ft. in the ground, for ¼ sec. cor. marked ¼ S on W face; from which
 A maple, 20" dia., bears N.87°E., 35 lks., mkd: ¼ S BT.
 A maple, 16" dia., bears N.37°W., 41 lks., mkd: ¼ S BT.

Ron Rice - For: Oxbow Timber 1 LLC - 3/1/2013 - C.S. 65/79-3

Set - 5/8"x 30" rebar with 2½" aluminum cap marked
 T20S R7W
 ¼
 S18|S17
 2013
 54633LS
18" D.Fir bears N.42°W., 7.8' blazed, scribed ¼ S18 BT
16" D.Fir bears S.44¾°W. 14.3' blazed, scribed ¼ S18 BT
14" D.Fir bears S.67¾°E. 17.4' blazed, scribed ¼ S17 BT
12" D.Fir bears N.55¾°E. 17.1' blazed, scribed ¼ S17 BT
Steel post adjacent to corner