

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 cor. Secs. 7 & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 628)

-----  
Set sandstone, 24x12x7", 18" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which  
A V.Maple, 5" dia., bears N.60°E., 9 lks., mkd: ¼ S BT.  
A V.Maple, 4" dia., bears S.11°W., 10 lks., mkd: ¼ S BT.

Ron Rice - For: Oxbow Timber 1 LLC - 3/1/2013 - C.S. 65/79-3

-----  
Set - 5/8"x30" rebar with 2½" aluminum cap marked  
T20S R7W  
¼  
S7|S8  
2013  
54633LS

The following accessories:

12" D.Fir bears S.46½°E., 6.1' blazed, scribed ¼ S8 BT  
14" D.Fir bears S.20¼°W., 26.5' blazed, scribed ¼ S7 BT  
12" D.Fir bears N.20°W., 8.8' blazed, scribed ¼ S7 BT  
16" D.Fir bears N.70½°E., 15.3' blazed, scribed ¼ S8 BT  
Steel post adjacent to corner

FD. Alum. cap & 4 BTs by R Rice 6/17/2015 - C.S. file 65/89-9