

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 628)

Set sandstone, 18x12x10" 12" in the ground for cor. to secs. 5, 6, 7, & 8, marked with 5 notches on S & 5 notches on E edges; from which

- A fir, 14" dia. bears S.84°E., 49 lks. mkd: T20S R7W S8 BT
- A maple, 7" dia. bears N.66°E. 56 lks. mkd: T20S R7W S5 BT
- A fir, 24" dia. bears S.45°W. 10 lks. mkd: T20S R7W S7 BT
- A maple, 6" dia. bears N.62°W. 42 lks. mkd: T20S R7W S6 BT

BLM dependent resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #350 & 622, surveyed Oct. 1966/May 1967 (DCSO rec. Vol. 34 Page(s) 14156-7)

The cor. of secs. 5, 6, 7, & 8, monumented with the broken orig. sandstone 12x8x3" lying on top of the ground with 5 notches on the E edge, from which the orig. BTs:

- An uprooted & burned maple stump, 10" dia., N.60°E., 53 lks., no marks visible (Rec. & slope dist., 56 lks.)
- A burned & dead fir, 27" dia, bears S.84°E., 49 lks., mkd. with a healed blaze.
- A burned & dead fir, 32" dia, bears S.35°W., 10 lks., with scribe mark S visible on partially opened blaze. (Rec. bearing S.45°W.)
- An uprooted & burned maple stump, 8" dia. bears N.62°W., 42 lks., no marks visible.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T20S R7W
<u>S 6 S 5</u>
S 7 S 8
1967

from which new BTs

- A sawed & burned fir stump, 55" dia., bears N.21½°E., 66 lks., mkd: T20S R7W S5 BT.
- A sawed & burned fir stump, 40" dia., bears N.28½°W., 92½ lks., mkd: T20S R7W S6 BT.

Deposit the cor. stone & set a steel fence post alongside the iron post.

From this point electronic survey control point, ABC 2, established during the Aerial Electronic Cadastral Resurvey in the Oxbow Ridge Fir Area, in 1967, bears N.50°43'E., 7.66 chs. monumented with an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd: ABC 2

+
1967

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which

A sawed & burned fir stump, 52" dia. bears N.41°E., 102½ lks., mkd: ABC 2 BT.

A sawed & burned fir stump, 55" dia., bears S.14°W., 71½ lks., mkd: ABC 2 BT.

BLM dependent resurvey by Daniel N. Patterson, Cadastral Surveyor under Group No. 2165, surveyed July 2007/Sept. 2008 - (DCSO records Vol. 56 Page(s) 22212-3)

The cor. of secs. 5, 6, 7, & 8, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd.

from which the remains of original bearing trees reported by Roseberry and Glenn in 1966-67

A burnt decayed fir stump, size indeterminate, bears S.84°E., 32.3 ft., with no marks visible.

A burnt decayed fir snag, 32" dia., bears S.35°W., 6.6 ft., with no marks visible on decayed opened blaze.

and the remains of bearing trees mkd. by Roseberry and Glenn

A burnt decayed fir stump, size indeterminate, bears N.21½°E., 43.6 ft., with no marks visible.

A burnt decayed fir stump, size indeterminate, bears N.28½°W., 61.1 ft., with no marks visible.

and new bearing trees

A fir, 9" dia. bears N.23¾°E., 5.4 ft. mkd. T20S R7W S5 BT

A fir, 12" dia. bears S.38¾°E. 5.3 ft. mkd. T20S R7W S8 BT

A fir, 9" dia. bears S.18°W., 21.1 ft. mkd. T20S R7W S7 BT

A fir, 7" dia. bears N.62¾°W. 10.7 ft. mkd. T20S R7W S6 BT

From this corner, a point established in 1967 for an electronic survey control point, ABC-2, during the Aerial Electronic Cadastral Resurvey in the Oxbow Ridge Fire Area, bears N.50°42'25"E.; 504.27 ft., monumented with an iron post, 2½" dia., firmly set, projecting 3" above the ground, with brass cap mkd. ABC-2

+
1967

from which the remains of bearing trees mkd. by Aerial Electronic Cadastral Resurvey

A burnt decayed fir stump, size indeterminate, bears N.41°E. 67.7 ft., with no marks visible.

A burnt decayed fir stump, size indeterminate, bears S.14°W., 47.2 ft., with no marks visible.

and new bearing trees

A fir, 9" dia., bears N.64¼°W., 6.6 ft., mkd. ABC 2 BT.

A fir, 13" dia., bears N.28½°E., 3.0 ft., mkd. ABC 2 BT.

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Rice - For: Oxbow Timber 1 LLC - 3/1/2013 - C.S. 65/79-3

Found - 1967 BLM brass cap with the following accessories:
9" D.Fir bears N.23 $\frac{3}{4}$ °E., 5.4' scribing visible
13" D.Fir bears S.38 $\frac{3}{4}$ °E., 5.3' healed face
11" D.Fir bears S.18°W., 21.1' healed face
8" D.Fir bears N.62 $\frac{3}{4}$ °W., 10.7' scribing visible

All other accessories noted in 2007-2008 BLM visitation are in same as noted condition. Station ABC-2 was not searched for.