

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 630)

-----  
Set sandstone, 12x12x7" 10" in the ground for the 1/4 sec. cor. marked 1/4 on W face; from which

A fir, 30" dia., bears S.47°W., 45 lks., mkd: 1/4 S BT.

A fir, 40" dia., bears S.89°E., 55 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #350 & 622, surveyed Oct. 1966/May 1967 (DCSO rec. Vol. 34 Page(s) 14157-8)

-----  
The 1/4 sec. cor. of secs. 5 & 6 determined at record bearing & distance from the orig. BTs:

A burned & sawed fir stump, 45" dia., bears S.89°E., 55 lks., with scribe marks 1/4 visible on partially opened blaze.

A burned & sawed fir stump, 45" dia., bears S.47°W., 45 lks., with a healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap marked:

T20S R7W

1/4

S 6 | S 5

1967

Set a steel fence post alongside the iron post.

Fd. & used on BLM Resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16126)