

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T19-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 566)

-----  
(Note from Pg. #564 - I here set a cor. common to 4 sections, but after I found the errors in the E. bdy. of the township, through which I found it necessary to set closing corners on the N. bdy. of the township, thus making this corner common only to 2 sections each)

Set a post 4 ft. long, 4' sq., 24" in ground for cor. to secs. 31 & 32, marked T19S R7W on N.; S32 on E.; S31 on W. faces, with 5 notches on E. & 1 notch on W. faces; also a sandstone, 20x18x10 ins., 16" in the ground, marked with 5 noches on E. & 1 notch on W. edges; from which

A Chittem 8" dia., bears N.29°E., 33 lks. dist. mkd. T19S R7W S32 BT.

A V.Maple 4" dia., bears S.15°W., 38 lks. dist. mkd. T19S R7W S31 & 32 BT.

A Chittem 4" dia., bears N.1°W., 21 lks. dist. mkd. T19S R7W S31 BT.

BLM Resurvey by Norman Price and Thomas Tillman, Cadastral Engineers, under Group #284, Surveyed June/Sept. 1949 - (DCSO records Vol. 31 Page(s) 13009-10)

-----  
The cor. of secs. 31 & 32, monumented with a disintegrating sandstone, 20x18x10 ins., firmly set, with only partial chisel marks remaining.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 19 S R 7 W

S 31 | S 32

T 20 S R 7 W

S 5

1949

from which new bearing trees:

A Fir 26" dia., bears N.82°45'E., 71 lks. dist. mkd. T19S R7W S32 BT.

A Fir 20" dia., bears N.13½°W., 91 lks. dist. mkd. T19S R7W S31 BT.

Deposit the sandstone at the base of the iron post.

BLM Resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16102)

-----  
The Sec. Cor., monumented with an iron post 2" dia., firmly set, projecting 12' above ground with brass cap mkd. in 1949, (Cont. Next Page)

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 209700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T19-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees mkd. by Price & Tillman:  
A Fir 45" dia., bears N.82 3/4°E., 71 lks. dist., with  
healed blaze.  
A Fir 27" dia., bears N.13½°W., 91 lks. dist. with healed  
blaze.  
Set a 5 ft. steel fence post alongside iron post.

---

Fd & used on M96-41 & C.S. File 58/289-2B by D. Baker 3/1984