TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 619)

Set post, 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on N face; from which
A fir, 16" dia., bears N.30°E., 10 lks., mkd: ¼ S BT.
A fir, 16" dia., bears S.4°W., 20 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Woolley Logging Co. - 1961 - C.S. File 51/222 & M 21-76

Found - Rock mkd: ¼S & 2 orig. BTs
Set - 1"x1"x36" T. Iron
36" Fir, N.73°E., 8.2 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike stone & Jerry Layne - Feb. 1966 - C.S. File 54/22-2

Found - Sandstone 4"x8"x12" mkd: "S¼" on S side & "X" on top not recorded in orig. notes.
Haines "T" iron & BT.
36" Fir N.73°E., 8.2 ft., down & shows scribe on partially healed scar.
Orig. 16" now 30" fir S.4°W., 13.2 ft., shows fair scar. Do not open.
Orig. 16" now 28" fir N.30°E., 6.6 ft., lying face down, scribe visible. We do not open.
Set - Brass cap at cor. mkd: County Surveyors T20S ¼ S 29 / S 32 Office, 1966
14" Hemlock N.63°E., 29.1 ft., mkd: ¼ S29 CS BT
8" Yew S.70½°E., 41.3 ft., mkd: ¼ S32 CS BT
Note - 9/8/1966, Corner OK - S edge of Oxbow Fire.

Mark Smalley - For: Roseburg Forest Products - Crew: Bill Olson & Ralph McMamis - 12/18/1996 - C.S. File 65/20-19

Found - 1966 DCSO brass cap.
14" Hemlock, N.63°E., 29', rotted stump.
8" Yew, S.70½°E., 41.3', down - alive.
36" Fir, N.73°E., 8.2', dead-down.
Set - 12" Hemlock, N.63°W., 16.5', scribed "¼ S29 BT"
13" Hemlock, N.79°W., 17.1', scribed "¼ S29 BT"
17" Hemlock, S.76°E., 53.6', scribed "¼ S32 BT"
12" Fir, S.28°W., 22.8', scribed "¼ S32 BT"

Fd. BC, 6 BTs and steel post by R Rice 3/2016 - M170-70