

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 622)

Set post, 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on N face; from which
 An Alder, 8" dia., bears South 31 lks., mkd: ¼ S BT. (in Gulch)
 A fir, 4" dia., bears N.8°W., 8 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Woolley Logging Co. - Filed April 1961 - M20-38

Found - No trace of orig. ¼ cor.
Set - Midway, 1"x1"x36" T iron
 18" fir N.26°W., 20.5 ft.
 28" fir S.34°W., 33.8 ft.

Les Roberts - For: International Paper Co. - June 1985 - C.S. File 63/18-1(B) & M 99-7

Found - Haines "T" iron, (1961) 1" dia.
 26" Fir, N.25°W., 21.0 ft. (scar vis.) 1961 BT rec.
 N.26°W., 20.5 ft.
 35" Fir, S.34°W., 32.0 ft. (scar vis.) 1961 BT rec.
 S.34°W., 33.8 ft.
New Accessories -
 Replaced "T" iron with 2½"x30" alum. pipe & cap.
 Buried purple magnetic marker under pipe. See filed survey for procedures.
 Set metal fence post, with survey monument sign wired to, beside alum. pipe.
Corner lies on South slope about 100' north of small creek.

Les Roberts - Seneca Jones Timber Co. - April 1999 - M131-45

Found - 2½" alum. pipe with alum. cap set by Les Roberts in survey M99-7.
 38" Fir, S.34°W., 32.0 ft., (scar vis.) 1961 BT (Haines 1961 BT NW BT is downed)
New BT - 8" Maple, N.9°E., 5.6' scribed/metal washer painted red)

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2699, surveyed May/Sept 2013 - (DCSO records Vol. 58 page(s) 23143-4)

The ¼ sec. cor. of secs. 20 and 29, reestablished by proportionate measurement by Haines, in 1961, and perpetuated by Roberts, in 1985; there is no remaining evidence of the orig. cor. and this position is accepted as a careful and faithful reestablishment of the cor., monumented with an aluminum post, 2½" dia., firmly set, flush with the ground with aluminum cap (properly) mkd.

from which a bearing tree mkd. by Haines

A fir, 44" dia., bears S.33¾°W., 33.1 ft., with a healed blaze.

and the remains of a bearing tree mkd. by Roberts

A maple snag, 10" dia., bears N.16½°E., 5.6 ft., with fragmentary scribe marks visible on a partially healed blaze.

and a new bearing tree

A fir, 12" dia., bears N.22½°W., 28.9 ft., mkd. ¼ S20 BT. Alongside the cor. is a T-shaped iron rod, ¾" dia., firmly set, flush with the ground, with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE