

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 20

Alias	Description

Les Roberts - International Paper - June 1985 - M99-7 & C.S.
File 63/18-1(C)

Set - 2½"x30" alum. pipe & cap. Buried purple magnetic marker
under pipe. See filed survey for procedures.
6" Fir, S.52°W., 12.9 ft. to spike (scribed/alum.
washer/painted)
8" Fir, N.52°W., 17.1 ft. to spike (scribed/alum.
washer/painted)
Metal fence post, with survey monument sign wired to,
beside alum. pipe.
Corner lies on steep north slope about 140' north of dirt
road.

BLM resurvey by George M. Winter, Cadastral Surveyor, under
Group No. 2699, surveyed May/Sept 2013 - (DCSO records Vol.
58 page(s) 23147)

The center ¼ sec. cor. of sec. 20, established by Roberts,
in 1985, and is accepted as the cor., monumented with an
aluminum post, 2½" dia., firmly set, projecting 4" above
ground, with aluminum cap (properly) mkd.
from which bearing trees mkd. by Roberts
A fir, 17" dia., bears S.54½°W., 12.9 ft., with a healed
blaze.
A fir, 19" dia., bears N.52°W., 17.1 ft., with a healed
blaze.

Ronald L Rice - For: Oxbow Timber 1 LLC - April 2015 - M170-3

Found - Alum. cap set by Roberts PLS 1039 dated 1985 with
the following accessories:
17" D.Fir bears S.54½°W., 12.9' - healed face.
19" D.Fir bears N.52W., 17.1' - healed face.
New - 14" D.Fir bears N.62°E., 18.0' - blazed, scribed C¼
S20 BT.
8" D.Fir bears S.56°E., 3.4' - blazed, scribed C¼
S20 BT.
Steel post adjacent to corner.