

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 624)

Set post, 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., mkd: 1/4 S on N face; from which
A fir, 50" dia., bears N.44°W., 36 lks., mkd: 1/4 S BT.
A fir, 30" dia., bears S.34°E., 29 lks., mkd: 1/4 S BT.

Wilford N. Haines - For: Woolley Logging Co. - Filed April 1961 - M20-38

Found - Orig. Fir BTs
Set - 1"x1"x36" T. iron.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage, J. Rabe, Frank Young - Sept 1966 - C.S. 54/22-10

Found - Haines "T" iron at corner.
Orig. 50"?, now 43" fir N.49°W. 23.8 ft. recorded as N.44°W. Alive, shows faint scar. We do not open.
Orig. 30"?, now 58" fir S.34°E. 19.1 ft. now snag we open & find "1/4" scribe at intersection of dist.
Set - Brass cap at cor. mkd: County Surveyors T20S R7W
Office 1/4 S 17
(Reset "T" iron alongside) 1966 S 20
New BTs- 41" D.Fir N.10°W., 44.2 ft. mkd: 1/4 S17 CS BT. Alive.
26" D.Fir S.39°W., 40.5 ft. mkd: 1/4 S20 CS BT. Alive.
Corner lies on NE slope approx. 50' E of top of spur, course SE.

Fd. Ok L. Roberts, 3/1985 - M99-7 & C.S. File 63/18-1(M)

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2699, surveyed May/Sept 2013 - (DCSO records Vol. 58 page(s) 23146-7)

The 1/4 sec. cor. of secs. 17 & 20, perpetuated by Haines, in 1961, further perpetuated by the Douglas County Surveyor's Office in 1966, monumented with an iron post, 1 1/4" dia., firmly set, flush with the ground, with brass cap (properly)mkd.

from which the remains of the original bearing trees
A fir stump, 60" dia., bears S.34°E., 19.1 ft., with a decayed blaze and no marks visible.
A fir stump, 32" dia., bears N.44°W., 23.8 ft., with no marks visible.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir stump, 24" dia., bears S.38¼°W., 40.5 ft., with no marks visible.
A fir stump, 36" dia., bears N.9½°W., 44.2 ft., with no marks visible.
and new bearing trees
A fir, 9" dia., bears S.22°W., 5.7 ft., mkd. ¼ S20 BT.
A fir, 9" dia., bears N.88°W., 6.5 ft., mkd. ¼ S17 BT.
Alongside the cor. is a T-shaped iron rod, 3/4" dia., firmly set, projecting 3" above ground, with faintly mkd. brass disk on top.