

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 626-7)

Set post, 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor. marked 1/4 S on N face; from which

A maple, 12" dia., bears S.44°W., 12 lks., mkd: 1/4 S BT.

A cedar, 18" dia., bears N.22°W., 25 lks., mkd: 1/4 S BT.

Ron Rice, NW Land Surveying - For: Oxbow Timber 1 LLC - June 2013 - M165-47

Set - 5/8"x30" REBAR WITH 2-1/2" ALUM. CAP

T20S R7W

1/4 $\frac{S\ 8}{S17}$

2013

54633LS

16" D.Fir bears S.85 3/4°E., 33.9' blazed scribed 1/4 S17 BT

15" D.Fir bears S.2 3/4°E., 8.0' blazed, scribed 1/4 S17 BT

18" D.Fir bears N.43°E., 12.0' blazed, scribed 1/4 S8 BT

18" D.Fir bears N.84°W., 33.3' blazed, scribed 1/4 S8 BT

Steel post adjacent to corner