

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 629)

Set post, 4 ft. long, 4x4x 24" in the ground, for ¼ sec. cor. marked ¼S on N face; from which

A fir, 14" dia., bears N.6°W., 12 lks., mkd: ¼ S BT.

A fir, 36" dia., bears S.87°E., 6 lks., mkd: ¼ S BT.

BLM dependent resurvey by Daniel N. Patterson, Cadastral Surveyor under Group No. 2165, surveyed July 2007/Sept. 2008 - (DCSO records Vol. 56 Page(s) 22211)

Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T20S R7W

¼ $\frac{S\ 5}{S\ 8}$

2008

from which

A fir, 12" dia., bears S.15°W., 10.7 ft., mkd. ¼ S8 BT

A fir, 12" dia., bears N.85¼°W., 21.3 ft., mkd. ¼ S5 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.