

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 5 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Resurvey by Harvey E. Wofford & Lester E. Fischer,  
Cadastral Surveyors, under Group #913, Surveyed Aug.  
1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16101)

-----  
Point for the ¼ sec. cor. of sec. 5 only, T20S R7W., at  
midpoint on the N. bdy. of sec. 5.

Set an iron post 28" long, 2½" dia., 14" in the ground, to  
solid rock, and in a mound of stone, 3 ft. base, to top, with  
brass cap mkd:

T 19 S R 7 W  
    ¼ S 5  
T 20 S R 7 W  
    1977

from which

A Fir 15" dia., bears S.5°E., 36 lks. dist. mkd. ¼ S5 BT.

A Fir 20" dia., bears S.71½°W., 32 lks. dist. mkd. ¼ S5  
BT.

Set a 5 ft. steel fence post alongside iron post.

Fd & used on M96-41 & C.S. File 58/289-2E by D. Baker 3/1984

BLM dependent resurvey by Daniel N. Patterson, Cadastral  
Surveyor under Group No. 2165, surveyed July 2007/Sept. 2008 -  
(DCSO records Vol. 56 Page(s) 22189)

-----  
The ¼ sec cor. of sec 5 only, T20S R7W established by Wofford &  
Fischer in 1976-78; monumented with an iron post, 2½" dia.,  
firmly set, projecting 4" above the ground, in a mound of stone,  
3 ft. base, 1 ft. high, with brass cap (properly) mkd.

from which bearing trees mkd. by Wofford and Fischer

A fir, 19" dia., bears S.5°E., 23.8 ft., with a healed  
blaze.

A fir, 27" dia., bears S.71½°W., 21.1 ft., with a healed  
blaze.