

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T19-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 565)

-----  
A sandstone in place, showing face 16x12 ins., 10" above ground, which I mark with cross (X) at exact corner point, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on N. face; from which  
A Fir 7" dia., bears N.30°W., 10 lks. dist. mkd.  $\frac{1}{4}$  S BT.  
A Fir 48" dia., bears S.20°E., 35 lks. dist. mkd.  $\frac{1}{4}$  S BT

BLM Resurvey by Norman Price and Thomas Tillman, Cadastral Engineers, under Group #284, Surveyed June/Sept. 1949 - (DCSO records Vol. 31 Page(s) 13009)

-----  
The  $\frac{1}{4}$  sec. cor. of sec. 32, monumented with a sandstone, 16x16x12 ins., firmly set, marked  $\frac{1}{4}$  S on N. face and with a cross on top, from which the original bearing trees:

A Fir 55" dia., bears S.10°E., 50 lks. dist., with blaze healed, but overgrowth partially burned. (Rec. S.20°E., 35 lks. dist.)

A Fir 28" dia., bears N.30°W., 10 lks. dist., plainly blazed and healed.

At the corner point

Set an iron post 3 ft. long, 1" dia., 28" in the ground with brass cap mkd:  $\frac{1}{4}$  S 32

1949

from which a new bearing tree:

A Fir 40" dia., bears N.59°E., 105 lks. dist., marked  $\frac{1}{4}$  S32 BT.

Deposit original stone at base of iron post.

BLM Resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16101)

-----  
The  $\frac{1}{4}$  sec. cor., monumented with an iron post, 1" dia., firmly set, projecting 10" above ground with brass cap mkd. in 1949, from which the original bearing trees:

A Fir 68" dia., bears S.10°E., 50 lks. dist., with healed blaze.

A Fir 37" dia., bears N.30°W., 10 lks. dist., with healed blaze.

and a bearing tree mkd. by Price and Tillman

a Fir 37" dia., bears N.59°E., 105 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside iron post.

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 249700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T19-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Fd & used on M96-41 & C.S. File 58/289-2A by D. Baker 3/1984

BLM dependent resurvey by Daniel N. Patterson, Cadastral Surveyor under Group No. 2165, surveyed July 2007/Sept. 2008 - (DCSO records Vol. 56 Page(s) 22188)

-----  
The ¼ sec. cor. of sec. 32 only, T19S R7W determined at record distance intersection from the remains of the original bearing trees

A fir, 79" dia., bears S.10°E., 33.0 ft. with a healed blaze.

A decayed fir stump, size indeterminate, bears N.30°W., 6.6 ft., with no marks visible.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T19S R7W  
¼ S 32  
T20S R7W  
2008

from which new bearing trees

A fir, 6" dia., bears N.83¼°W., 14.8 ft., mkd. ¼ S32 BT.

A fir, 5" dia., bears N.31°W., 12.5 ft., mkd. X BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.