

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 610)

Set a sandstone 16x16x8", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A fir, 24" dia., bears N.56°W., 12 lks., mkd: ¼ S BT.

A fir, 24" dia., bears S.31°E., 18 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Stephen J. Flaue - Mike Koch -Sept. 27, 2012 - C.S. File 67/36-27

REPORTED AS NOT FOUND

Many stones approximating the orig. monument size are examined; no evidence of markings described is found.

(Search area was defined mid-way point between the orig. NW & SW corners of sec. 28)

Due to pass logging all OBTs would now be stumps. We open many candidate OBT stumps in a wide search area but find no evidence of blazes or scribing.

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2699, surveyed May/Sept 2013 - (DCSO records Vol. 58 page(s) 23139-40)

Point for the ¼ sec. cor. of secs. 28 & 29, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T20S R7W
¼
S29|S28
2013

from which

A fir, 9" dia., bears N.75¼°E., 10.3 ft., mkd. ¼ S28 BT.

A fir, 13" dia., bears S.21¾°W., 11.2 ft., mkd. ¼ S29 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.