

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28 & 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 611)</p> <p>-----</p> <p>Set sandstone, 24x16x8" 18" in the ground for cor. to sec. 20, 21, 28 & 29 marked 2 notches on S & 4 notches on E edges; from which</p> <ul style="list-style-type: none">A cedar, 36" dia., bears S.69°E., 64 lks., mkd: T20S R7W S28 BT.A fir, 24" dia. bears N.25°E. 41 lks. mkd: T20S R7W S21 BTA cedar, 30" dia., bears S.51°W., 15 lks., mkd: T20S R7W S29 BT.A hemlock, 10" dia., bears N.69°W., 79 lks., mkd: T20S R7W S20 BT.
<p>Wilford N. Haines - For: Woolley Logging Co. - Filed April 1961 - M20-38</p> <p>-----</p> <p>Found - NE BT, Fir, standing. NW Hemlock BT standing SE Cedar down. SW Cedar a snag.</p> <p>Scribed- 24" R.Cedar N.16°W., 71.4 ft. Set - 1"x1"x36" T. iron.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage, J. Rabe, Frank Young - Sept 1966 - C.S. 54/22-8</p> <p>-----</p> <p>Found - "T" iron & BT Orig. 10" now 34" Hemlock N.69°W., 52.1 ft., burned out inside. No scribe fd. Alive. Haines BT, 24" R.Cedar N.16°W., 71.4 ft. dead, burned, scribe burned off. Haines button on face. All other BTs destroyed.</p> <p>New BTs- (only slightly burned, both alive) 24" Hemlock N.81°W. 67.0 ft. mkd: T20S R7W S20 CS BT 22" D.Fir S.86°W., 94.9 ft. mkd: T20S R7W S29 CS BT</p> <p>Note - No other BTs available due to Oxbow burn. Corner lies on South slope, approx. 150 ft. N of small creek, cors. west.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - May 6, 1968 - C.S. File 54/22-13</p> <p>-----</p> <p>Found - "T" iron & BTs Also steel fence post. 24" Hemlock N.81°W., 67.0 ft. now high stumped, drive 5/8"x30" I.R. in ground below blaze.</p> <p>continued next page</p>

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

22" D.Fir, S.86°W., 94.9 ft. now turned out & slid downhill.
Set - Brass cap at cor. mkd: County Surveyors Office T20S R7W S 20|S 21 S 29|S 28
New BT - 63" D.Fir stumps S.80°E., 120.1 ft. mkd: "T20S R7W S28 CS BT" (Drive 5/8"x30" I.R. 18" into center of a stump)
Reset "T" iron & steel fence post alongside brass cap.
This corner lies on S slope approx. 150 ft. N of small creek, corners West.

Fd. Ok L. Roberts, 3/1985 M99-7 & C.S. File 63/18-1(L)

David Edwards - For. Seneca Jones Timber Co. - Nov. 2012 - M164-39

Found - Brass cap
Haines' 24" cedar snag, N.16°W., 71.4'
Steel fence post S.21°E., 1.6'
New BTs scribed per BLM Manual -
15" dia., Fir S.54°E., 5.2'
12" dia., Fir S.35°W., 11.2'
Set - 6 ft. steel post 2' north.

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2699, surveyed May/Sept 2013 - (DCSO records Vol. 58 page(s) 23140-1)

The cor. of secs. 20, 21, 28, & 29, perpetuated by Haines, in 1961, further perpetuated by the Douglas County Surveyor's Office in 1966 and 1968 and by Edwards, in 2012, monumented with an iron post, 1¼" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd.
from which the remains of an original bearing tree
A trace of a decayed stump, bears N.69°W., 52.1 ft.
and the remains of a bearing tree mkd. by Haines
A cedar snag, 24" dia., bears N.17¼°W., 61.0 ft., with a burnt blaze.
and the remains of a BT mkd. by the Douglas County Surveyor's Office in 1966
A decayed hemlock stump, size indeterminate, bears N.80¼°W., 67.0 ft., with a steel reinforcing rod set alongside and no marks visible.
and the remains of a BT mkd. by the Douglas County Surveyor's Office in 1968

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed stump, 63" dia., bears S.85¼°E., 120.1 ft., with a steel reinforcing rod set in the center and no marks visible.

and bearing trees mkd. by Edwards

A fir, 15" dia., bears S.48°E., 5.2 ft., with scribe marks T20S R7W S28 BT visible on an open blaze.

A fir, 12" dia., bears S.39°W., 11.2 ft., with scribe marks T20S R7W S29 BT visible on an open blaze.

and new bearing trees

A fir, 9" dia., bears N.31°E., 16.3 ft mkd T20S R7W S21 BT

A fir, 13" dia., bears N.68°W., 8.7 ft mkd T20S R7W S20 BT

A search was made for the original line tree bet. secs. 28 and 29 and it was not recovered.

Alongside the cor. is a T-shaped iron rod, 3/4" dia., firmly set, projecting 14" above ground, with faintly mkd. brass disk on top.