

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 612)

Set sandstone, 24x12x10" 18" in the ground for the ¼ sec. cor. marked ¼ on W face; from which

A maple, 12" dia., bears S.70°E., 24 lks., mkd: ¼ S BT.

A fir, 36" dia., bears West, 58 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & BLM - Sept. 1966 - C.S. File 54/22-3

Found - Sandstone 24"x14"x12" mkd: "X" on top & "¼" on W face
Orig. 36" now 50" Fir west 38.8 ft., down & burned,
we open on underside & find "4 B" scribe.

No trace of other orig. BT.

Set - Brass cap at cor. mkd: County Surveyors T20S R7W
Office 1966 ¼ S20/S21

Reset rock alongside BC

New BTs- 8" Hemlock S.2°W., 27.8 ft., mkd: ¼ S20 CS BT

11" Maple snag N.69°E., 12.0 ft., mkd: ¼ S21 CS BT

Note - No live trees available. Corner lies approx. 130 ft.
N of creek, course S.60°W.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - May 6, 1968 - C.S. File 54/22-14

Found - C.S. brass cap in place.

Orig. BT as recorded in 1966.

Renewal BTs both gone due to logging.

Steel fence post has been set by brass cap.

Since there are no trees for several hundred feet, we mark stumps as follow:

50" D.Fir stump N.76°E., 25.2 ft. mkd: ¼ S21 CS BT"

(Set 5/8"x30" I.R. 20" deep in center of stump)

50" Fir stump N.76°W., 54.7 ft. mkd: ¼ S20 CS BT"

(Set 5/8"x30" I.R. 20" deep in center of stump)

This corner lies approx. 80 ft. N of creek, course S.60°W.,
& 150 ft. N of log access road parallel to creek

Fd. Ok by Les Roberts 3/1985 - M99-7 & C.S. File 63/18-1(N)

BLM resurvey by George M. Winter, Cadastral Surveyor, Group No. 2699, surveyed May/Sept 2013 - (DCSO rec Vol. 58 pgs 23141-2)

The ¼ sec. cor. of secs. 20 & 21, perpetuated by the Douglas Co Surveyor's Office in 1966 & 1968, monumented with an iron post, 1¼" dia., firmly set, buried 4" below ground, with brass cap (properly) mkd. continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an original bearing tree
A trace of root fragments bears West, 38.3 ft.
and the remains of BTs mkd. by the Douglas Co Surveyor's
Office in 1968

A fir stump, 60" dia., bears N.80¼°E., 25.2 ft., with a
steel reinforcing rod set in the center, with illegible
scribe marks visible.

A fir stump, size indeterminate, bears N.76¾°W., 56.6 ft.,
with a steel reinforcing rod set in the center, with no
marks visible.

and new bearing trees

A fir, 9" dia., bears S.82¼°E., 24.7 ft., mkd. ¼ S21 BT.

A fir, 10" dia., bears N.8¼°W., 15.8 ft., mkd. ¼ S20 BT.