

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 614)

Set a post, 4 ft. long, 4" square, 24" in the ground, for cor. to secs. 8, 9, 16, & 17, marked T20S S9 on NE R7W S16 on SE, S17 on SW, S8 on NW faces, with 4 notches on S & E edges; from which

- A fir, 40" dia. bears N.64°E., 17 lks. mkd: T20S R7W S9 BT
- A fir, 28" dia. bears S.38°E., 9 lks. mkd: T20S R7W S16 BT
- A fir, 50" dia. bears S.10°W. 17 lks. mkd: T20S R7W S17 BT
- A fir, 28" dia. bears N.29°W., 55 lks. mkd: T20S R7W S8 BT

BLM dependent resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #350 & 622, surveyed Oct. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14153)

The cor. of secs. 8, 9, 16, & 17, determined at record bearing & dist. from the remains of the orig. BTs:

- An uprooted & burned fir, 50" dia., bears N.64°E., 17 lks., no marks visible.
- A burned fir snag, 28" dia., S.38°E., 9 lks., with burned blaze, no scribe marks visible. Rescribed T20S R7W S16 BT on new blaze.
- A stump hole, bears S.10°W., 17 lks.
- An uprooted & burned fir, 43" dia., bears N.29°W., 55 lks. with scribe marks S8 visible on partially opened blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T20S	R7W
<u>S 8</u>	<u>S 9</u>
S 17	S 16
1967	

from which new BTs

- A sawed & burned fir stump, 70" dia., bears S.48°W., 60½ lks., mkd: T20S R7W S17 BT.
- A sawed & burned fir stump, 36" dia., bears N.24½°W., 64 lks., mkd: T20S R7W S8 BT.

No other suitable trees available within limits
Set a steel fence post alongside the iron post.

Ron Rice, NW Land Surveying - For: Oxbow Timber 1 LLC - June 2013 - M165-47

Found - BLM brass cap dated 1967, with the following accessories:

28" burned D.Fir snag bears S.38°E., 5.9' scribing visible.

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

70" burned D.Fir stump bears S.48°W., 39.9' scribing visible.
36" burned D.Fir stump bears N.24½°W., 42.2' - no marks.
New BTs- 18" D.Fir bears N.3°E., 34.0' - blazed, scribed T20S R7W S9 BT
16" D.Fir bears S.38°W., 49.2' - blazed, scribed T20S R7W S17 BT