

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 615-6)

-----  
Set a post, 4 ft. long, 4" square, 24" in the ground, for cor. to secs. 4, 5, 8, & 9, marked T20S S4 on NE R7W S9 on SE, S8 on SW, S5 on NW faces, with 5 notches on S & 4 on E edges; from which  
A fir, 48" dia. bears N.21°E., 47 lks. mkd: T20S R7W S4 BT  
A vine maple, 4" dia., bears S.65°E., 27 lks., mkd: T20S R7W S9 BT.  
A hemlock, 20" dia., bears S.64°W., 66 lks., mkd: T20S R7W S8 BT.  
A maple, 12" dia., bears N.46°W., 47 lks., mkd: T20S R7W S5 BT.

BLM dependent resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #350 & 622, surveyed Oct. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14154)

-----  
The cor. of sec. 4, 5, 8, & 9, determined at record dist. from the remaining orig. BTs:  
A hemlock snag, 33" dia., bears S.58½°W., 66 lks., with fragmentary scribe marks visible on partially opened blaze. (Rec. S.64°W.)  
A maple snag, 23" dia., bears N.59°W., 47 lks., with fragmentary scribe marks visible on partially opened blaze. (rec. N.46°W.)

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:  
T20S R7W  
S 5 | S 4  
S 8 | S 9  
1967

from which new BTs  
A sawed & burned fir stump, 50" dia., bears N.23½°E., 63 lks., mkd: T20S R7W S4 BT.  
A burned cedar, 50" dia., bears S.28½°W., 85 lks., mkd: T20S R7W S8 BT.  
A burned fir, 45" dia., bears N.71°W., 41 lks., mkd: T20S R7W S5 BT.  
No other suitable tree available within limits.  
Set a steel fence post alongside the iron post.

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by Daniel N. Patterson, Cadastral Surveyor under Group No. 2165, surveyed July 2007/Sept. 2008 - (DCSO records Vol. 56 Page(s) 22208)

-----

The cor. of secs. 4, 5, 8, & 9, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd. from which the remains of an original bearing tree reported by Roseberry and Glenn in 1966-67

A burnt decayed hemlock snag, size indeterminate, bears S.58½°W., 43.6 ft., with no marks visible. and the remains of bearing trees by Roseberry and Glenn

A burnt decayed fir stump, 50" dia., bears N.19¼°E., 41.6 ft., with scribe marks T20S R7W S4 BT visible on open blaze. (Record, N.23½°E.)

A burnt decayed fir stump, 45" dia., bears N.71°W., 27.1 ft., with no marks visible. and new bearing trees

- A fir, 13" dia. bears N.13°E. 16.4 ft. mkd. T20S R7W S4 BT
- A fir, 9" dia. bears S.28½°E. 41.3 ft. mkd. T20S R7W S9 BT
- A fir, 10" dia. bears S.30°W. 14.7 ft. mkd. T20S R7W S8 BT
- A fir, 11" dia. bears N.62¾°W. 9.1 ft. mkd. T20S R7W S5 BT

The geographic position (NAD 1983 (CORS 96)) of these corners as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:  
The corner of sections 4, 5, 8, and 9.  
Latitude: 43°51'04.17"N. Longitude: 123°32'54.59"W.

Fd. BC & 7 BTs w/steel post adjacent to corner by R.Rice 5/2014 - M168-5