

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 617-18)

-----  
I set a sandstone 18x10x8 ins., 12" in the ground for closing cor. to secs. 4 and 5, marked CC with 4 notches on E. and 2 notches on W. faces; from which

A Fir 48" dia., bears S.70°E., 100 lks. dist., mkd. T20S R7W S4 BT.

A Fir 60" dia., bears S.8°W., 43 lks. dist., mkd. T20S R7W S5 BT.

A Fir 55" dia., bears N.24°E., 74 lks. dist., mkd. T20S R7W CC S4 & 5 BT.

BLM Resurvey by Norman Price and Thomas Tillman, Cadastral Engineers, under Group #284, Surveyed June/Sept. 1949 - (DCSO records Vol. 31 Page(s) 13008)

-----  
(Corner report only)

The closing cor., monumented with a sandstone 18x10x8 ins., 12" above ground, marked X on top, CC on N. face, with 2 grooves on W. face and 4 grooves on E. face; and with an iron bar, 1" dia., 20" above ground, firmly set, from which the original bearing trees:

A Fir 60" dia., bears N.24°E., 22 lks. dist., plainly blazed and healed. (Rec. distance 74 lks.)

A Fir 52" dia., bears S.78°E., 89 lks. dist., with blaze partially exposed and decayed. (Rec. brg. S.70°E., 100 lks. dist.)

A Fir 54" dia., bears S.8°W., 43 lks. dist., plainly blazed and healed.

BLM Resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16124)

-----  
True point for the closing cor. of secs. 4 and 5.

Set an iron post 28" long, 2½" dia., 26" in the ground, with brass cap mkd:

T 19 S R 7 W  
S 32  
S 5 | S 4  
T 20 S R 7 W  
C C  
1977

from which

A Fir 6" dia., bears S.31½°E., 15 lks. dist., mkd. T20S R7W S4 CC BT.

(Cont. Next Page)

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir 7" dia., bears S.62°W., 10 lks. dist. mkd. T20S R7W  
S5 CC BT.

Set a 5 ft. steel fence post alongside iron post.

From this point, the original closing cor. of secs. 4 and 5,  
bears N.0°12"., 0.02 chs. dist., monumented with an iron rod,  
1" dia., firmly set, projecting 20" above ground, from which  
the remains of the original bearing trees:

A sawed Fir stump 48" dia., bears N.24°E., 22 lks. dist.  
with axe marks visible on opened and burned blaze.

A root hole, bears S.8°W., 43 lks. dist., with a down Fir  
alongside 54" dia., no marks visible.

Fd & used on M96-41 & C.S. File 58/289-2C by D. Baker 3/1984

BLM dependent resurvey by Daniel N. Patterson, Cadastral  
Surveyor under Group No. 2165, surveyed July 2007/Sept. 2008  
- (DCSO records Vol. 56 Page(s) 22187)

-----  
The closing cor. of secs. 4 and 5, T. 20 S., R. 7 W.,  
established by Wofford and Fischer in 1976-78; monumented  
with an iron post, 2½" dia., firmly set, projecting 3" above  
the ground, with brass cap (properly) mkd.

from which the bearing trees mkd. by Wofford and Fischer

A fir, 20" dia., bears S.31½°E., 9.9 ft., with a healed  
blaze.

A fir, 17" dia., bears S.62°W., 6.6 ft., with a healed  
blaze.

From this corner, the original closing cor. of secs. 4 and 5,  
bears N.0°09'58"W., 1.32 ft., monumented with an iron rod, 1"  
dia., firmly set, projecting 2" above the ground; from which  
the remains of original bearing trees

A decayed fir stump, 48" dia., bears N.24°E., 14.5 ft.,  
with no marks visible.

A root hole, bears S.8°W., 28.4 ft., alongside of which is  
lying a decayed fir, size indeterminate, no marks  
visible.