

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 314100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 557)

Set post 6" dia., 4 ft. long, with marked stone, 12" in ground, for closing cor. to secs. 4 & 5, marked T20S R7W S33 on N. face; R7W S4 on SE.; T21S S5 on SW. face, with 2 notches on the W. and 4 on the E. edge, from which
A Maple 24" dia., bears N.27°E., 14 lks. dist. mkd. T20S R7W S33 BT.
A Cedar 30" dia., bears S.34°E., 49 lks. dist. mkd. T21S R7W S4 BT.
A Fir 50" dia., bears S.37°W., 20 lks. dist. mkd. T21S R7W S5 BT.

Fd. OK and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 573-74)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - 1962 - C.S. File 49/89-37

Found - 70" Fir snag, S.37°W., 13.2 ft., faint bark scribing visible.
36" Cedar, uprooted, down and dead, S.34°E., 32.3 ft. Cut open and found scribing.
No trace of Maple to NE.
30" Hemlock N.24°W., 13.0 ft., old scribing visible in previously opened scar, "BT S33 T20", looks like original but no record of this tree.
24" Red Cedar N.84°W., 21.1 ft., recent scribing fd.
Set Brass cap at cor. mkd: County Surveyors Office
T 21 S R 7 W
S 5 | S 4
1962
New BTs- 5" D.Fir S.79°E., 19.3 ft. mkd. S4 CS BT.
Rescribe 70" Fir snag, S.37°W., 13.2 ft. (in bark)
"T21S R7W S5 CS BT".
Haines "T" Iron bears N.17°W., 4.0 ft. Corner is on level ground approx. 75 ft. East of Smith River Road.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1159, surveyed Aug. 1983/May 1984 - (DCSO records Vol. 47 Page(s) 18038-39)

The Sec. Cor., perpetuated and recorded by Godfrey in 1962, monumented with an iron post 1¼' dia., firmly set, projecting
(Cont. Next Page)

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 314100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" above ground, with brass cap mkd. in 1962,
from which the remains of an original bearing tree:
A sawed Fir stump 67" dia., bears S.37°W., 20 lks. dist.,
no marks visible.
and bearing trees mkd. by person(s) unknown and recorded by
Godfrey:
A Cedar 29" dia., bears N.84°W., 32 lks. dist., with frag-
mentary scribe marks visible on opened blaze.
A Hemlock 38" dia., bears N.24½°W., 21 lks. dist., with
fragmentary scribe marks visible on partially healed
blaze.
and a bearing tree mkd. by Godfrey:
A Fir 17" dia., bears S.78½°E., 29 lks. dist., with healed
blaze.

From this point, a point established by Wilford N. Haines, LS
#239, during an unrecorded survey, bears N.18¼°W., 0.06 chs.
dist., monumented with a 1" "T" shaped iron rod, firmly set,
projecting 5" above ground.
(Note: See Haines field book, H-64 for possible information.)