

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 340140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Secs. 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Wayne Rogers & Lance J. Bishop, Cadastral Surveyor, under Group #1159, surveyed Aug.1983/ May 1984 - (DCSO records Vol. 47 Page(s) 18046-7)

-----  
The point for the center ¼ sec. cor. of sec. 33, at intersection with the E & W centerline.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T20S R7W  
C ¼ S 33  
1984

from which

A sandstone outcrop, 10x10 ft., bears N.87½°E., 74 lks., mkd: X BO

A hemlock, 12" dia. bears S.82°W., 76 lks. mkd: C¼ S33 BT

A fir, 23" dia., bears N.21°W., 99 lks., mkd: C¼ S33 BT.

-----  
Les Roberts, LS #1039 - Sept. 2, 1989 - C.S. File 63/85-40

Found - 1984 BLM brass cap set firmly in the ground in recently logged unit.

11" hemlock stump, S.84°W., 48.6 ft. (scar vis.) 1984 BT.

20" fir stump, N.20°W., 65.1 ft. (scar vis) 1984 BT

Set - 72" alum. post, with land survey sign bolted to, beside BC.

New RP - 20" cedar stump, S.77°W., 46.1 ft. to spike driven into base of stump, stump not scribed.

Soaked sides & tops of stumps with a wood preservative.

Covered tops of stumps with 0.020 thick sheets of alum.