

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 609-10)

Set a post, 3" sq., 4 ft. long, 2 ft. in ground, for 1/4 sec. cor., marked 1/4 S on N face; from which
A leaning Alder, 20" dia., bears South 3 lks.
An Ash, 20" dia., bears N.12°W., 25 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by Wayne Rogers & Lance J. Bishop, Cadastral Surveyor, under Group #1159, surveyed Aug.1983/ May 1984 - (DCSO records Vol. 47 Page(s) 18045)

Point for 1/4 sec. cor. of secs. 28 & 33, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:
T20S R7W
S 28
S 33
1984

from which
An Alder, 19" dia., bears S.73 1/2°W., 55 lks. mkd: 1/4 S33 BT.
A cedar, 46" dia., bears N.48 3/4°W., 197 lks. mkd: 1/4 S28 BT.

Fd. BC & 2 BTs by D.Edwards 11/2012 - M164-39