

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 613)

Set post, 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on N face; from which
A fir, 48" dia., bears N.70°W., 28 lks., mkd: ¼ S BT.
A fir, 48" dia., bears S.20°W., 37 lks., mkd: ¼ S BT.

BLM dependent resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #350 & 622, surveyed Oct. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14141)

Point for ¼ sec. cor. of secs. 16 & 21, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T20S R7W
¼ S 16
S 21
1966

from which
A fir, 12" dia., bears N.54½°E., 66½ lks., mkd: ¼ S16 BT.
A fir, 20" dia., bears S.3°E., 54 lks., mkd: ¼ S21 BT.
Set a steel fence post alongside the iron post.
The cor. is located on top of ascent, slopes S.