

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only, T19-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 564)

-----  
Set Chittem post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face; from which  
A Cedar 24" dia., bears S.81°E., 45 lks. dist. mkd. ¼ S BT.  
A Fir 12" dia., bears N.40°W., 9 lks. dist. mkd. ¼ S BT.

BLM Resurvey by Norman Price and Thomas Tillman, Cadastral Engineers, under Group #284, Surveyed June/Sept. 1949 - (DCSO records Vol. 31 Page(s) 13007)

-----  
The ¼ sec. cor. of sec. 33, determined at the record bearing and distance from both original bearing trees as follows:  
A Cedar 36" dia., bears S.81°E., 45 lks. dist., plainly blazed and healed.  
A Fir 28" dia., bears N.40°W., 9 lks. dist., plainly blazed and healed.  
At the corner point  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: ¼ S 33  
1949  
from which a new bearing tree  
A Fir 50" dia., bears N.60°E., 80 lks. dist. mkd. ¼ S33 BT

BLM Resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16099-100)

-----  
The ¼ sec. cor. of sec. 33 only, determined from the remains of an original bearing tree:  
A sawed Cedar stump 36" dia., bears S.81°E., 45 lks. dist., no marks visible.  
and the remains of a bearing tree mkd. by Price & Tillman:  
A burned sawed Fir stump 53" dia., bears N.60°E., 80 lks. dist., with scribe marks ¼ visible on open burned blaze.  
At the corner point  
Seat a brass tablet, 3¼" dia., 3 1/2" stem, in drill hole, in solid rock, with to mkd. T 19 S R 7 W  
¼ S 33  
1977  
No suitable trees available within limits.  
Set a 5 ft. steel fence post alongside brass tablet.