

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 573)

-----  
Set sandstone 16x16x16 ins. 12" in the ground for cor. to secs. 33 & 34, marked with 3 notches on E. & W. faces, from which

A Fir 24" dia., bears S.6°W., 30 lks. dist. mkd. T20S R7W S33 & 34 BT.

A Fir 36" dia., bears N.57°W., 15 lks. dist. mkd. T20S R7W S33 BT.

A Fir 18" dia., bears N.32°E., 106 lks. dist. mkd. T20S R7W S34 BT.

-----  
Wilford N. Haines, #239 & Leo Martin - For: Harold Woolley - Filed Jan. 21, 1958 - M 8-31

-----  
Set Lot Marker from original BTs.

-----  
Douglas Co. Surveyors Office - Gary L. Langlitz; P. Earle, crew - Feb. 11, 1974 - C.S. File 56/43-23

-----  
Found - Orig. 36" now 38" D.Fir with scribing "20S R7W S33" showing on previously opened blaze.

A tagged Fir to the NE. does not fit proper bearing and distance.

Set brass cap at record brg. & dist. from OBT, mkd:

County Surveyors Office 1974

T 20 S R 7 W

S 33 | S 34

T21S

from which:

Orig. 36" now 38' D.Fir bears N.57°W., 9.9 ft.

A 1"x1" T-Iron with copper washer attached mkd. Wilford N Haines 239 Survey Point Drain Oregon, bears S.25½°W., 3.6 ft.

New BTs- An 8" Red Cedar bears N.65½°E., 11.8 ft. scribed T20S R7W S34 CS BT.

A 6" Red Cedar bears n.47°W., 22.0 ft. scribed T20S R7W S33 CS BT.

-----  
BLM Resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, Group #1159, Surveyed Aug. 1983/May 1984 - (DCSO records Vol. 47 Page(s) 18036-37)

-----  
The Sec. cor., perpetuated and recorded by Langlitz in 1974, monumented with an iron pipe 1¼" dia., firmly set, projecting 6" above ground, from which the remains of the original bearing trees:  
(Cont. Next Page)

