

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 599)

Set fir post, 4 ft. long, 4" sq. 24" in the ground, for ¼ sec. cor., mkd. ¼ S on W face; from which
An alder, 7" dia., bears S.43°E., 23 lks., mkd: ¼ S BT.
A fir, 6" dia., bears N.10°W., 6 lks., mkd: ¼ S BT.

Wilford N. Haines - Feb. 1965 - C.S. File 51/309-1

Found - Fir with good scar N.10°W., 6 lks.
Rock for corner.
Set - 1"x1"x36" "T" iron by rock & scribed:
8" Fir S.56¾°E., 18.0 ft.
14" Fir S.89°W., 6.6 ft.

BLM Dependent resurvey by Wayne Rogers & Lance J. Bishop, Cadastral Surveyor, under Group #1159, surveyed Aug.1983/ May 1984 - (DCSO records Vol. 47 Page(s) 18041-2)

The ¼ sec. cor. of secs. 33 & 34, perpetuated & recorded by Haines in 1965, monumented with a 1" "T" shaped iron rod, firmly set, projecting 6" above ground, from which the remaining OBT:

A Fir, 22" dia., bears N.10°W., 6 lks., with healed blaze. and BTs mkd. by Haines

A Fir, 9" dia, bears S.59¼°E., 28 lks., with healed blaze.

A Fir, 16" dia. bears N.89°W., 10½ lks. with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with aluminum cap marked:

T20S R7W
¼
S 33 | S34
1983