

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 600)

Set a post, 4 ft. long, 4" square, 24" in the ground, for cor. to secs. 27, 28, 33, & 34, marked T20S S27 on NE R7W S34 on SE, S33 on SW, S28 on NW faces, with 1 notch on S & 3 notches on E edges; from which
A fir, 48" dia. bears N.42°E. 14 lks. mkd: T20S R7W S27 BT
A chittem, 4" dia., bears S.35°E., 32 lks., mkd: T20S R7W S34 BT.
A V.Maple, 4" dia., bears S.11½°W., 28 lks., mkd: T20S R7W S33 BT.
A chittem, 4" dia., bears N.43°W., 33 lks., mkd: T20S R7W S28 BT.

Wilford N. Haines - For: Woolley Logging - Feb. 10, 1965 - M29-19

Set - 1"x1"x36" "T" iron from orig. Fir BT, now down.
10" Maple N.80°W., 51.4 ft.
12" Hemlock N.8½°E., 51.5 ft.
14" Alder S.14°W., 23.0 ft.
18" Alder S.62½°E., 10.5 ft.

BLM Dependent resurvey by Wayne Rogers & Lance J. Bishop, Cadastral Surveyor, under Group #1159, surveyed Aug.1983/ May 1984 - (DCSO records Vol. 47 Page(s) 18044)

The cor. of secs. 27, 28, 33, & 34, perpetuated & recorded by Haines in 1965, monumented with a 1" "T" shaped iron rod, firmly set, projecting 10" above ground, from which the remains of an orig. BT:
A sawed fir stump, size indeterminate, bears N.42°E., 14 lks., no marks visible.
and the remains of BTs mkd. by Haines
A sawed Hemlock stump, 18" dia., bears N.8°E., 78 lks., with healed blaze.
A sawed Alder stump, 16" dia., bears S.64°E., 16 lks., with scribe marks S34 T20S R7W BT visible on bark.
A sawed Alder stump, 16" dia., bears S.13°W., 48 lks., with scribe marks S33 T20S R7W BT visible on bark.
A sawed Maple stump, size indeterminate, bears N.79¾°W., 79 lks., no marks visible.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>T20S R7W <u>S 28 S 27</u> S 33 S 34 1983</p> <p>from which new BTs & reference monuments</p> <p>An iron post, 28" long, 2½" dia., set 24" in the ground for a reference monument, bears N.40°E., 50 lks., with brass cap mkd: RM T20S R7W S27 1984, and an arrow pointing to the corner.</p> <p>An iron post, 28" long, 2½" dia., set 24" in the ground for a reference monument, bears S.40°E., 50 lks., with brass cap mkd: RM T20S R7W S34 1984, and an arrow pointing to the corner.</p> <p>A fir, 19" dia., bears S.29½°W., 407 lks., mkd: T20S R7W S33 BT.</p> <p>A maple, 9" dia., bears N.11¾°W., 568 lks., mkd: T20S R7W S28 BT.</p>
<p>Fd. Ok by D. Edwards, 10/1995 - M122-71 Fd. Ok by D. Edwards, 6/1998 - M130-2</p>