

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 601)

-----  
Set post, 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S on W face; from which

A fir, 8" dia., bears S.27°E., 38 lks., mkd: ¼ S BT.

A fir, 6" dia., bears S.17°W., 39 lks., mkd: ¼ S BT.

-----  
David Edwards - For: Roseburg Resources - June 1998 - M 130-2  
- C.S. File 65/18-2 A&B

-----  
Set - 3½" dia., brass cap on aluminum post.

8" dia. Chinquapin, bears N.78°E., 15.22'.

7" dia. Fir, bears S.40°W., 16.33'.

10" dia. Fir, bears., S.88½°W., 20.14'.

10" dia. Chinquapin, bears N.52°W., 6.15'.

Note- BTs are scribed according to the 1972 BLM Manual, are measured to the center of tree at root crown.