

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 601-2)

-----  
Set a post, 4 ft. long, 4" square, 24" in the ground, for cor. to secs. 21, 22, 27, & 28, marked T20S S22 on NE R7W S27 on SE, S28 on SW, S21 on NW faces, with 2 notches on S & 3 on E edges; from which

- A fir, 40" dia. bears N.69°E. 71 lks. mkd: T20S R7W S22 BT
- A fir, 48" dia. bears S.3°E., 84 lks. mkd: T20S R7W S27 BT
- A fir, 48" dia. bears S.36°W. 19 lks. mkd: T20S R7W S28 BT
- A fir, 36" dia. bears N.13°W. 27 lks. mkd: T20S R7W S21 BT

-----  
David A. Edwards, for Pete Hopkins, Oct. 1995 - M122-71; CS File 63/100-4

-----  
This corner was determined by proportion and lies in a large clearcut and therefore no bearing trees could be scribed. The corner itself falls on the nearly vertical face of a large boulder and could not be monumented.

New Accessories -

- Reference monuments set are 5/8" x 30" steel pins with red plastic cap mkd. "D.A. EDWARDS-LS 2339"
- Ref. mon. bears N.2°23'00"E., 27.24 ft.
- Ref. mon. bears N.59°17'13"E., 24.50 ft.
- Ref. mon. bears S.36°14'31"E., 16.13 ft.
- Ref. mon. bears S.69°03'32"W., 36.62 ft.

Fd. Ok by D. Edwards 6/1998 M130-2