

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 604-5)

-----  
Set sandstone, 18x16x6" 12" in the ground for the 1/4 sec. cor. marked 1/4 on W face; from which

A Fir, 30" dia., bears S.65°W., 92 lks., mkd: 1/4 S BT.

A Fir, 4" dia., bears S.13°E., 36 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #350 & 622, surveyed Oct. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14150)

-----  
The 1/4 sec. cor. of secs. 15 & 16, determined at record bearing & distance from the remaining orig. BT:

A stump hole, bears S.13°E., 36 lks., with an uprooted & burned fir, 22" dia, lying downhill with scribe marks 1/4 visible on partially open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

T20S R7W  
1/4  
S 16 | S 15  
1966

from which new BTs

A burned maple, 12" dia., bears N.10°E., 21 lks., mkd: 1/4 S15 BT.

A burned fir, 53" dia., bears S.61°W., 111 lks., mkd: 1/4 S16 BT.

Set a steel fence post alongside the iron post.

BLM dependent resurvey by Daniel N. Patterson, Cadastral Surveyor under Group No. 2165, surveyed July 2007/Sept. 2008 - (DCSO records Vol. 56 Page(s) 22198)

-----  
The 1/4 sec. cor. of secs. 15 and 16, remonumented by Roseberry and Glenn in 1966-67 and determined at record distance intersection from the remains of bearing trees mkd. by Roseberry and Glenn.

A root hole, bears N.10°E., 13.9 ft., alongside of which is lying a decayed maple, 14" dia., with scribe marks 1/4 S BT visible on opened blaze.

A burnt decayed fir stump, size indeterminate, bears S.59 3/4°W., 73.3 ft., with no marks visible. (Record, S.61°W.)

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd.

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T20S R7W  
¼  
S 16|S 15  
2008

from which new bearing trees

A hemlock, 4" dia., bears N.49¼°E., 22.6 ft., mkd. X BT.

An alder, 16" dia., bears N.4°W., 6.9 ft., mkd. ¼ S16 BT  
on bark.

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.