

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 606)

Set sandstone, 16x12x6" 12" in the ground for the ¼ sec. cor. marked ¼ on W face; from which

A madrone (arbutus), 6" dia., bears N.35°W., 32 lks., mkd: ¼ S BT.

A maple, 3" dia., bears S.60°E., 45 lks., mkd: ¼ S BT.

State of Oregon, Dept. of Forestry, Wiljo E. Green - March 1967 - C.S. File 55/36 & M34-10

Reestablished by single prop. measurement.

Set - Ore. St. Bd. of Forestry 1½"x36" gal. IP, 33" in ground, from which:

20" burnt fir stump S.87°W., 12.0 ft. with YMLP

20" burnt fir S.50°E., 20.0 ft. YMLP

4"x4"x72" white painted cedar post NW 1.0 ft.

BLM dependent resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #350 & 622, surveyed Oct. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14151)

The ¼ sec. cor. of secs. 9 & 10, monumented by the Oregon State Board of Forestry, in 1967, with an iron post, 1½" dia., firmly set, projecting 4" above the ground, with bronze cap mkd.

OREGON STATE BOARD OF FORESTRY

S 9 | S 10

1967

from which BTs by Oregon State Board of Forestry

A sawed & burned fir stump, 25" dia., bears S.44°E., 9 lks., with scribe marks ¼ S9 BT visible on open blaze.

A burned fir, 30" dia. bears N.89°W., 32 lks., with scribe marks ¼ S10 BT RS 563 visible on open blaze.

and a new BT

A burned fir, 12" dia., bears S.59½°W., 54½ lks., mkd: ¼ S9 BT.

Set a steel fence post & a 4" sq., 4 ft. long, white wooden post alongside the iron post.

Ronald L. Rice - For: Oxbow Timber 1 LLC - May 2014 - M168-5

Found - Ore. State Board of Forestry brass cap dated 1967 with the following accessories;

25" D.Fir stump bears S.44°E., 21.1' (rec. 9 lks) scribing visible

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 11" D.Fir bears N.15°W.,, 30.0' scribed "¼ S9 BT"
16" D.Fir bears S.61°E., 12.3' scribed "¼ S10 BT"
8" D.Fir bears S.0°E., 1.5' scribed "X BT"
11" D.Fir bears N.89°W., 9.7' scribed "¼ S9 BT"
Steel post adjacent to corner