

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 607)

-----  
Set sandstone, 18x16x7", 12" in the ground, for cor. to secs. 3, 4, 9 & 10, marked with 5 notches on S & 3 notches on E edges; from which

- A fir, 36" dia. bears N.76°E. 75 lks. mkd: T20S R7W S3 BT.
- A fir, 20" dia. bears S.12°E. 54 lks. mkd: T20S R7W S10 BT
- A fir, 24" dia. bears S.87°W. 54 lks. mkd: T20S R7W S9 BT
- A fir, 30" dia. bears N.19°W., 8 lks. mkd: T20S R7W S4 BT

-----  
State of Oregon, Dept. of Forestry, Wiljo E. Green - March 1967 - C.S. File 55/36 & M34-10

-----  
Found - Orig. stone, now missing, from which a:  
36" Fir bears S.12°E., 54 lks.; now 30" burnt tree with scribed "T 2" visible.  
24" Fir bears S.87°W., 54 lks; now 30" burnt tree with scribes "S 9" visible.  
30" Fir bears N.19°W., 8 lks; now 36" burnt & down with face grown over.

Set - 1½"x36" gal. IP with 3" br. cap mkd: Ore. St. Bd. of Forestry T20S R7W S3 S4 S9 S10 1967 RS563", 30" in gr., in edge of hole of uprooted NW BT & from which a:  
38" Burnt Fir bears S.66°W., 50.6 ft.; scribed T20S R7W S10 BT RS563.  
44" Burnt Fir bears N.26°E., 28.4 ft.; scribed T20S R7W S3 BT.  
36" Burnt Fir bears N.60°W., 38.5 ft.; scribed T20S R7W S4 BT.

Set - 4"x4"x72" white painted Cedar post, 1 ft. SE of corner pipe. Ore. St. Forestry Dept. metal location poster on NE BT.  
This corner on the Douglas-Lane County Line.

-----  
BLM dependent resurvey by Lynn M. Roseberry & Wm. W. Glenn, Cadastral Surveyors, under Group #350 & 622, surveyed Oct. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14151)

-----  
The cor. of secs. 3, 4, 9 & 10, monumented by the Oregon State Board of Forestry, in 1967, with an iron post, 1½" dia., firmly set, projecting 5" above the ground, with bronze cap mkd.

OREGON STATE BOARD OF FORESTRY

S 4	S 3
S 9	S 10
1967	

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the orig. BTs  
A burned Fir, 40" dia., bears N.76°E., 25 lks., with scribe mark T visible on partially opened blaze. (Rec. 75 lks.)  
A burned Fir, 30" dia., bears S.12°E., 54 lks., with a burned blaze.  
A burned Fir, 31" dia., bears S.87°W., 54 lks., with scribe marks W S9 visible on partially opened blaze.  
An uprooted Fir, 34" dia., bears N.19°W., 8 lks., with healed blaze.  
and BTs by Oregon State Board of Forestry  
A burned fir, 45" dia., bears N.27°E., 45 lks., with scribe marks T20S R7W S3 visible on unhealed blaze.  
A burned fir, 45" dia., S.66°E., 77½ lks., with scribe marks T20S T7W S10 BT visible on unhealed blaze.  
A burned fir, 34" dia., bears N.59°W., 61 lks., with scribe marks T20S R7w S4 BT visible on unhealed blaze.  
No other suitable trees available within limits.  
Set a steel fence post alongside the iron post.

BLM dependent resurvey by Daniel N. Patterson, Cadastral Surveyor under Group No. 2165, surveyed July 2007/Sept. 2008 - (DCSO records Vol. 56 Page(s) 22204-5)

-----  
The cor. of secs. 3, 4, 9, and 10, perpetuated by Wiljo E. Green, in 1967; monumented with an iron post, 1½" dia., firmly set, projecting 3" above the ground, with brass cap (properly) mkd.  
from which the remains of the original bearing trees reported by Roseberry and Glenn in 1966-67  
A decayed burnt fir stump, 40" dia., bears N.76°E., 16.5 ft., with illegible scribe marks visible on partially open blaze.  
A decayed burnt fir stump, 32" dia., bears S.12°E., 35.6 ft., no marks visible.  
A decayed burnt fir stump, 35" dia., bears S.87°W., 35.6 ft., with a healed blaze.  
and the remains of bearing trees mkd. by Green and reported by Roseberry and Glenn  
A decayed burnt fir stump, 43" dia., bears N.27°E., 29.7 ft., with illegible scribe marks visible on partially open blaze.  
A decayed burnt fir stump, 46" dia., bears S.66°E., 51.2 ft., with illegible scribe marks visible on partially open blaze.  
A decayed burnt fir stump, 44" dia., bears N.59°W., 40.3 ft., with illegible scribe marks visible on partially open blaze.  
continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees

A fir, 13" dia. bears N.35°E. 12.3 ft. mkd. T20S R7W S3 BT

A fir, 11" dia., bears S.45¼°E., 9.7 ft., mkd. T20S R7W  
S10 BT.

A fir, 10" dia. bears S.15¼°W. 6.6 ft. mkd. T20S R7W S9 BT

A fir, 7" dia. bears N.18¼°W. 16.1 ft. mkd. T20S R7W S4 BT

Fd. BC & 10 BTs w/steel post adjacent to corner by R. Rice,  
5/2014 - M168-5