

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 607)

Set cedar post, 4 ft. long, 4" square, 24" in the ground, for 1/4 sec. cor. marked 1/4S on W. face; from which

A cedar, 12" dia., bears N.87°W., 8 lks., mkd: 1/4 S BT.

An alder, 20" dia., bears N.72°E., 15 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Daniel N. Patterson, Cadastral Surveyor under Group No. 2165, surveyed July 2007/Sept. 2008 - (DCSO records Vol. 56 Page(s) 22206)

Point for the 1/4 sec. cor. of secs. 3 & 4, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd.

T20S R7W

1/4

S 4 | S 3

2007

from which

A fir, 17" dia., bears S.33 3/4°E., 31.1 ft., mkd. 1/4 S3 BT.

A fir, 11" dia., bears S.84 3/4°W., 36.7 ft., mkd. 1/4 S4 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.