

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 572)

Marked sandstone in place, 24x24 ins. face in side of hill, for ¼ sec.cor., marked with cross (X) at exact corner point, ¼ on N. face; from which
A Fir 30" dia., bears N.65°E., 35 lks. dist. mkd. ¼ S BT.
A Maple 6" dia., bears S.75°W., 44 lks. dist. mkd. ¼ s BT.

Wilford N. Haines, #239 - For: Woolley Logging - Feb. 10, 1965 - M 29-29

Found "X" on rock. Fir BT is down. Maple is gone.
Drove "T" iron in ground, 1.1 ft. North of "X".
Scribed 28" Fir, N.77°W., 99.5 ft.

Douglas Co. Surveyors Office - Gary L. Langlitz; P. Earle, crew - Feb. 5, 1974 - C.S. File 56/43-8

Found - "X" chiseled on large sandstone boulder.
1" x 1" T-Iron bears North, 1.1 ft.
Rec. 28" now 30" D.Fir bears N.77°W., 99.5 ft. Shows well healed scar.
New BT - 30" D.Fir bears N.19°W., 99.6 ft. scribed ¼ S34 CS BT.

BLM Resurvey by Wayne L. Rogers & Lance J. Bishop - Cadastral Surveyors under Group #1159, Surveyed Aug. 1983/May 1984 - (DCSO records Vol. 47 Page(s) 18035)

The ¼ sec. cor., perpetuated and recorded by Haines in 1965, further perpetuated and recorded by DCSO in 1974, monumented with the original sandstone, 24x24 ins., x 2 ft. above ground, mkd. X on top, from which the remains of a bearing tree and a reference monument mkd. by Haines:

A 1" T shaped iron rod, firmly set, projecting 10" above ground, bears North, 2 lks. dist., with a washer 1" dia., mkd. Wilford N Haines 239 Survey Point Drain Oregon.

A sawed Fir stump, 34" dia., bears N.77°W., 151 lks. dist. with scribe marks BT visible on open blaze.

and the remains of a bearing tree mkd. by DCSO:

A sawed Fir stump 32" dia., bears N.19°W., 151 lks. dist. with healed blaze.

Seat a brass tablet, 3½" dia., ¾" stem, in drill hole at point of X in the corner stone, with brass tablet mkd.

(Cont. Next Page)

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>T 20 S R 7 W <u>¼ S 34</u> T 21 S R 7 W 1983</p> <p>from which a new bearing tree and bearing object: A Fir 4" dia., bears N.87½°E., 13 lks. dist. mkd. X BT. A rock outcrop 10x10 ft. bears N.26°W., 116 lks. dist. mkd. X B0.</p>
<p>Craig Wanless - For: Seneca Jones Tmbr Co. - 9/2005 - M148-50 ----- Found - 3½" brass tablet firmly cemented in orig. stone with USBLM cap dated 1983 A steel T-post, North 1.3 ft. rec. North 1.1 ft. - 1965 M29-19 32" Fir stump, N.77°W., 99.2 ft. with healed blaze, rec. N.77°W., 99.5 ft. - 1965 M29-19 32" Fir stump N.19°W., 99.6 ft. with healed blaze rec. N.19°W., 99.6 ft. - 1974 CS 56/43 14" Fir, N.87½°E., 8.6 ft. with healed blaze rec. N.87½°E., 13 lks. - 1983 BLM BT An "X B0" chiseled into solid rock N.26°W., 76.5 ft. rec. N.26°W., 116 lks - 1983 BLM</p> <p>New - 5" Fir, N.4°W., 15.5 ft. to steel spike at side center scribed "¼ S34 BT" 10" Fir N.48½°W., 36.9 ft., to steel spike at side center scribed "¼ S34 BT"</p>
<p>2</p>