

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 600-1)

Set a cedar post, 4 ft. long, 4" sq., 2 ft. in the ground, for ¼ sec. cor. marked ¼ S on N face; from which
A cedar, 60" dia., bears S.28°W., 55 lks., mkd: ¼ S BT.
A cedar, 48" dia., bears N.23°E., 105 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Woolley Logging - Feb. 10, 1965 - M29-19

Found - Stump of orig. BTs:
Cedar S.28°W., 55 lks.
Cedar N.23°E., 105 lks.
Scribed- 12" Fir N.49½°E., 26.0 ft.
16" Fir S.49½°E., 7.1 ft.

BLM Dependent resurvey by Wayne Rogers & Lance J. Bishop, Cadastral Surveyor, under Group #1159, surveyed Aug.1983/ May 1984 - (DCSO records Vol. 47 Page(s) 18049)

The ¼ sec. cor. of secs. 27 & 34, perpetuated & recorded by Haines in 1965, monumented with a 1" "T" shaped iron rod, firmly set, projecting 18" above ground, from which the remains of the orig. BTs:
A roothole, bears N.23°E., 105 lks.
A sawed cedar stump, 60" dia., bears S.28°W., 55 lks., no marks visible.
and BTs mkd. by Haines
A fir, 16" dia. bears N.48°E., 39½ lks. with healed blaze.
A fir, 28" dia. bears S.51°E., 11½ lks. with healed blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: T20S R7W
S 27
S 34
1983

Fd. Ok by D. Edwards, 10/1995 - M122-71
Fd. Ok by D. Edwards, 6/1998 - M130-2